



STONETECH® High Gloss Finishing Sealer

DS 219.5-0516

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

STONETECH® High Gloss Finishing Sealer

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: +1.888.786.6343

Fax: +1.203.393.1684

Website: www.laticrete.com

3. PRODUCT DESCRIPTION

STONETECH High Gloss Finishing Sealer protects and transforms the surface to a high shine finish.

Uses (Interior Only)

- Backsplashes
- Floors
- Walls

Advantages

- Provides brilliant shine and deepens color
- Protects against water and oil based stains
- Interior use
- Water-based formula
- Available in high-gloss and semi-gloss finish

Recommended Surfaces:

Natural stone and masonry surfaces such as:

- Slate
- Textured Limestone
- Textured Travertine
- Concrete
- Saltillo Tile

- Bluestone
- Sandstone
- Flagstone

Limitations

Not intended for use on glazed, polished, honed, or non-absorbing surfaces, wood floors and decks, showers, countertops and near pool areas.

Item Numbers and Packaging

D15145298 - Sample 2oz (59mL), 12 units per Case

D15145307 - Quart 32oz (946 mL), 6 units per Case, 600 units per Pallet

D15145318 - Gallon (3.8 L), 4 units per Case, 160 units per Pallet

Products Available for Sale in Canada Only:

D15226458 - Quart 32oz (946 mL), 6 units per Case, 600 units per Pallet

Approximate Coverage

- Up to 300 ft² per gallon (27.9 m²/3.8L), depending on the porosity of the surface
- Up to 75 ft² per quart (7 m²/946ml), depending on the porosity of the surface

Expected Wear

- Up to 5 years. Touch up on higher traffic areas may be required on a more frequent basis.

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

VOC Content

<85 g/L

Storage and Handling Instructions

CAUTION: MAY CAUSE RESPIRATORY IRRITATION. Do not ingest. Avoid prolonged exposure to vapors. Use in a well-ventilated area. For repeated or professional use, an approved respirator and gloves are recommended. Consult MSDS. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not release to natural waterways.

Cautions

Consult SDS for more safety information.

- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
- Skin contact: Wash skin with soap and water. Get medical attention if symptoms occur.
- Eye contact: Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if symptoms persist.
- Ingestion: Rinse mouth. Do not induce vomiting. Get medical attention if any discomfort continues.

4. TECHNICAL DATA

Physical Properties

Form	Liquid
Color	White
Odor	Slight acrylic-like
pH	8.7
Specific Gravity	1.013

Working Properties

Full Cure	24 – 48 hours
-----------	---------------

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine appropriate application method, achievement of desired results, and to ensure good adhesion. Surface must be thoroughly clean, dry, and free of any sealers or coatings before application. Application to a dirty or dusty surface will affect adhesion and appearance. Avoid applying in direct sunlight, surface temperature should be 50°F–80°F (10°C–26°C). STONETECH® High Gloss Finishing Sealer should not be applied to a wet or moist surface. Avoid applying onto surfaces not intended for treatment. For new installations with grout, sealer can be applied as soon as 72 hours after grouting. Fresh concrete slabs require a minimum of 28 days to cure before applying the sealer. Keep children and pets out of the area until treated surface is dry.

Directions

1. SHAKE WELL BEFORE USING. Do not dilute before applying.
2. Liberally apply 1-3 even coats of STONETECH High Gloss Finishing Sealer with a natural bristle paint brush, paint roller, low pressure sprayer, or pump-up garden sprayer. Avoid puddling of product during application.
3. Allow 30-45 minutes between coats or until the surface is dry.
4. Surface traffic may begin 12 hours after final application; keep installation dry for a minimum of 12 hours; full cure is achieved in 24-48 hours.
5. Keep surfaces clean and dry as finished surfaces may become slippery when wet.
6. Clean tools used during application immediately with water.

6. AVAILABILITY AND COST

Availability

LATICRETE, STONETECH and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

www.stonetech.com or www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, and/or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, and a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com or www.stonetech.com.

10. FILING SYSTEM

Additional product information is available on our website at www.stonetech.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 211.0: STONETECH Stone & Tile Cleaner

DS 215.0: STONETECH KlenzAll Cleaner

TDS 262: Stone and Tile Care Guide

LATICRETE International, Inc.
One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com
©2016 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.