

**Fila Chemicals USA**

Revision nr. 5

Dated 2/26/2018

**EPOXY PRO**

Printed on 22/03/2019

Page n. 1/14

Replaced revision:4

## Safety data sheet according to U.S.A. Federal Hazcom 2012

### 1. Identification

**1.1. Product identifier**

Product name

**EPOXY PRO****1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use

**CLEANER FOR EPOXY RESIDUES****Identified Uses****Industrial****Professional****Consumer**

Uses

-

**1.3. Details of the supplier of the safety data sheet**

Name

**Fila Chemicals USA.**

Full address

**10800 NW 21st St Ste # 170**

District and Country

**Miami, FL 33172****Tel. (305) 513-0708****Fax. (305) 513-0728****filausa@filasolutions.com**

e-mail address of the competent person

responsible for the Safety Data Sheet

**sds@filasolutions.com****1.4. Emergency telephone number**

For urgent inquiries refer to

**800-424-9300 CHEMTREC**

### 2. Hazards identification

**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Hazard pictograms:

Eye irritation, category 2

Causes serious eye irritation.





## Fila Chemicals USA

Revision nr. 5

Dated 2/26/2018

### EPOXY PRO

Printed on 22/03/2019

Page n. 2/14

Replaced revision:4

Signal words: Warning

#### Hazard statements:

**H319** Causes serious eye irritation.

#### Precautionary statements:

##### Prevention:

**P264** Wash hands thoroughly after handling.  
**P280** Wear eye protection / face protection.

##### Response:

**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P337+P313** If eye irritation persists: Get medical advice / attention.

##### Storage:

--

##### Disposal:

--

#### 2.2. Other hazards

Information not available

### 3. Composition/information on ingredients

#### 3.1. Substances

Information not relevant

#### 3.2. Mixtures

##### Contains:

Identification	x = Conc. %	Classification:	Trade secret:
<b>Phenylmethanol</b>			§
CAS 100-51-6	$10 \leq x < 20$	Acute toxicity, category 4 H302, Acute toxicity, category 4 H332, Eye irritation, category 2 H319	
EC 202-859-9			
INDEX 603-057-00-5			
<b>Propylene glycol n-propyl ether</b>			§
CAS 1569-01-3	$1 \leq x < 5$	Flammable liquid, category 3 H226, Eye irritation, category 2 H319	
EC 216-372-4			
INDEX -			
<b>Monoethanolamine oleate</b>			§
CAS 2272-11-9	$1 \leq x < 5$	Eye irritation, category 2 H319	
EC 218-878-0			



## EPOXY PRO

INDEX -

**Alanine, N,N-bis(carboxymethyl)-  
trisodium salt**

§

CAS 164462-16-2

 $1 \leq x < 2$ Substance or mixture corrosive to metals,  
category 1 H290

EC 423-270-5

INDEX -

Note: Upper limit is not included into the range.

§ The exact percentage (concentration) of composition has been withheld as a trade secret.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## 4. First-aid measures

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## 5. Fire-fighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE


Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

	Fila Chemicals USA	Revision nr. 5
	EPOXY PRO	Dated 2/26/2018 Printed on 22/03/2019 Page n. 4/14 Replaced revision:4

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## 8. Exposure controls/personal protection

### 8.1. Control parameters

TLV of solvent mixture: 7.5 mg/m<sup>3</sup>

**EPOXY PRO****8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

**HAND PROTECTION**

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Recommended material: Nitrile, minimum 0.38 mm thickness or equivalent protective barrier material with a high level performance for continuous contact conditions, with a minimum permeability time of 480 minutes in accordance with the CEN EN 420 and EN standards 374.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	Light yellow
Odour	Pine fragrance
Odour threshold	Not available
pH	10.8
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 93 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available

**EPOXY PRO**

Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not available
Solubility	Readily soluble
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

**9.2. Other information**

VOC 9,6%

**10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL

Avoid exposure to: air,sources of heat,naked flames.

**EPOXY PRO****10.5. Incompatible materials**

BENZYL ALCOHOL

Incompatible with: sulphuric acid, oxidising substances, aluminium.

**10.6. Hazardous decomposition products**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

**11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Alanine, N,N-bis(carboxymethyl)-, trisodium salt

LD50 (Oral) &gt; 4 mg/kg rat

LD50 (Dermal) &gt; 4 mg/kg dermal

LC50 (Inhalation) &gt; 5 mg/l rat

BENZYL ALCOHOL

**EPOXY PRO**

LD50 (Oral) 1230 mg/kg Rat

LD50 (Dermal) 2000 mg/kg Rabbit

LC50 (Inhalation) > 4.1 mg/l/4h Rat

**SKIN CORROSION / IRRITATION**

Does not meet the classification criteria for this hazard class

**SERIOUS EYE DAMAGE / IRRITATION**

Causes serious eye irritation

**RESPIRATORY OR SKIN SENSITISATION**

Does not meet the classification criteria for this hazard class

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

91-64-51,2-BENZOPYRONE

IARC:3

8006-64-2TURPENTINE

ACGIH::

5989-27-5D LIMONENE

IARC:3

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

**STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class



**EPOXY PRO****12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

Alanine, N,N-bis(carboxymethyl)-,trisodium salt

LC50 - for Fish > 200 mg/l/96h

EC50 - for Crustacea > 200 mg/l/48h

**12.2. Persistence and degradability**

BENZYL ALCOHOL

Rapidly degradable

**12.3. Bioaccumulative potential**

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1.1

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**13. Disposal considerations****13.1. Waste treatment methods**


Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**14. Transport information**

	Fila Chemicals USA	Revision nr. 5
	EPOXY PRO	Dated 2/26/2018 Printed on 22/03/2019 Page n. 10/14 Replaced revision:4

These goods must be transported by vehicles authorized to transport hazardous materials according to the provisions set out in the current regulations of the U.S. DOT, Canadian TDG, the IMDG and IATA.

#### Rail and Truck Shipments

DOT Shipping Name:	Not regulated
DOT ID Number	None
DOT Hazard Class & Packing Group	None
DOT Shipping Label	None

TDG Shipping Name:	Not regulated
TDG ID Number	None
TDG DOT Hazard Class & Packing Group	None
TDG Shipping Label	None

#### Water Shipments

IMO Shipping Name:	Not regulated
IMO ID Number	None
IMO DOT Hazard Class & Packing Group	None
IMO Shipping Label	None
IMO EMS	None

#### Air Shipments

IATA Shipping Name:	Not regulated
IATA ID Number	None
IATA DOT Hazard Class & Packing Group	None
1	None
IATA Packing Instructions	None

## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### U.S. Federal Regulations

##### TSCA:

##### Clean Air Act Section 112(b):

No component(s) listed.

##### Clean Air Act Section 602 Class I Substances:


No component(s) listed.

##### Clean Air Act Section 602 Class II Substances:

No component(s) listed.

##### Clean Water Act – Priority Pollutants:

No component(s) listed.

	Fila Chemicals USA	Revision nr. 5
	EPOXY PRO	Dated 2/26/2018 Printed on 22/03/2019 Page n. 11/14 Replaced revision:4

Clean Water Act –  
Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

25322-68-3

POLYETHYLENGLYCOL (Glycol  
ethers)

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

1310-58-3

POTASSIUM HYDROXIDE

EPCRA 313 TRI:

25322-68-3

POLYETHYLENGLYCOL (Glycol  
ethers)

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachusetts:

100-51-6

BENZYL ALCOHOL

141-43-5

ETHANOLAMINE

Minnesota:

100-51-6

BENZYL ALCOHOL



## Fila Chemicals USA

Revision nr. 5

Dated 2/26/2018

### EPOXY PRO

Printed on 22/03/2019

Page n. 12/14

Replaced revision:4

141-43-5

ETHANOLAMINE

#### New Jersey:

141-43-5

ETHANOLAMINE

#### New York:

No component(s) listed.

#### Pennsylvania:

100-51-6

BENZYL ALCOHOL

141-43-5

ETHANOLAMINE

#### California:

141-43-5

ETHANOLAMINE

#### Proposition 65:

#### International Regulations

#### Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

#### Substances subject to the Rotterdam Convention:

None

#### Substances subject to the Stockholm Convention:

None

#### Canadian WHMIS

Information not available


## 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>H226</b>	Flammable liquid and vapour.
<b>H290</b>	May be corrosive to metals.
<b>H302</b>	Harmful if swallowed.
<b>H332</b>	Harmful if inhaled.
<b>H319</b>	Causes serious eye irritation.

#### LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number

	Fila Chemicals USA	Revision nr. 5
	EPOXY PRO	Dated 2/26/2018 Printed on 22/03/2019 Page n. 13/14 Replaced revision:4

- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

#### GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112© of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.


This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

MSDS are subject to change without notice.

Changes to previous review:

	<b>Fila Chemicals USA</b>	Revision nr. 5
	<b>EPOXY PRO</b>	Dated 2/26/2018 Printed on 22/03/2019 Page n. 14/14 Replaced revision:4

The following sections were modified:  
01 / 02 / 03 / 04 / 05 / 07 / 11 / 12 / 15 / 16.