

CEMENTITIOUS GROUT HAZE REMOVER



ETERDEK

**PORCELAIN AND CERAMIC TILE, ACID RESISTANT STONE,
QUARRY TILE, TERRACOTTA**

BIODEGRADABLE



WHAT IT'S FOR

- Eliminates cementitious grout haze, efflorescence, lime deposits and hard water stains.
- Removes soap scum, rust stains, paint and construction dirt.
- Use indoors and outdoors on floors, walls, shower stalls, bathroom fixtures and facades.
- Safe on acid resistant stone, porcelain, ceramic tile and terracotta.
- Ideal for post-installation cleaning: it removes inorganic construction dirt.

ADVANTAGES

- Concentrated formula: high coverage.
- Eco-friendly: does not emit fumes that are harmful to people or the environment. A welcome alternative to muriatic acid.
- Does not alter the color of the material.
- Does not damage or corrode aluminum and steel trims when used according to the application instructions.
- Can be used as a cleaner or limescale remover, based on the dilution.
- Biodegradable.

HOW TO USE IT

POST INSTALLATION CLEANING: Wet the surface and grout joints with water, then use **ETERDEK** diluted 1:5 (1 QT of product in 5 QT of water). Apply the solution to sections of a few square feet at a time. Let sit a few minutes, then rub vigorously with an abrasive pad or large brush. Remove the residue with a cloth or wet vac and rinse with plenty of water. Should any stubborn dirt remain, repeat the application with a more concentrated solution.

OUTDOOR CLEANING: On surfaces with outdoor contaminants (smog, dust, etc.), dilute 1:10 (1 QT of product in 2.5 GAL of water). Then follow the application instructions above.

Caution: Do not use on acid sensitive stone such as marble, limestone, or travertine. Test the product on a small, inconspicuous area of the surface or loose sample prior to full application.

Storage temperature: between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

ELIMINATES CEMENTITIOUS GROUT HAZE, EFFLORESCENCE, LIME DEPOSITS, HARD WATER STAINS, RUST STAINS AND PAINT.

IDEAL FOR POST-INSTALLATION CLEANING: REMOVES INORGANIC CONSTRUCTION DIRT.



Coverage:

(1 GAL - 3.78 L)

Porcelain › Dilution 1:5

1,615 sq.ft. (150 m²)

Acid resistant natural stone › 1:5-1:10

815-1,430 sq.ft. (76-132 m²)

Terracotta › Dilution 1:5

410-815 sq.ft. (38-76 m²)

Coverage rates are indicative.



Packaging:

1 GAL (3.78 L) 4 plastic bottles per box

1 QT (946 ml) 12 plastic bottles per box