

INSTANT CLEANER FOR FRESH CEMENT GROUT

INSTANT REMOVER

BIODEGRADABLE

PORCELAIN AND CERAMIC TILE. GLASS MOSAIC. OUARRY TILE





Eliminates fresh cement grout residue during installation, before it

WHAT IT'S FOR

- Effective on grout with additives.
- Ideal for cleaning the back of large format tile prior to installation.
- Perfect for cleaning grouting tools.

ADVANTAGES

- Dries quickly, to be used during installation.
- No foam, no rising necessary.
- Does not damage grout joints.
- Does not damage or corrode aluminum and steel trims.
- Use indoors and outdoors, ideal for floors and vertical surfaces.
- High coverage.
- Safe for the installer and the environment: does not emit harmful fumes.

- DOES NOT FOAM.
- SAFE FOR THE INSTALLER AND THE **ENVIRONMENT.**
- NO RINSING NECESSARY.

Coverage:

24 OZ (710 ml)

Porcelain and ceramic tile > Up to 161 sq. ft. Large format tile > Up to 1.148 linear feet Mosaic > Up to 161 sq. ft.

Coverage rates are indicative.



REV. 01

Packaging:

24 OZ (710 ml) 12 spray bottles per box

HOW TO USE IT

READY TO USE. Wait for the grout to initially set and become firm to the touch (usually about 10 to 30 minutes, according to the grout manufacturer's instructions). Carry out an initial cleaning of the surface with a damp sponge. Then, spray **INSTANT REMOVER** and let sit for 1-2 minutes. For textured tile, let sit for 5-10 minutes. Clean using a sponge trowel, rinsing it often to keep it clean. For stubborn stains, repeat the above instructions after one hour. Refer to the grout manufacturer's instructions for indications about when the surface is safe to use.

To clean the back of large format tile: Spray INSTANT REMOVER on a soft sponge and wipe the back of the tile.

Caution: Do not use on acid sensitive materials. Do not use abrasive sponges. Test the product before use to determine the material's resistance and the dwell time required for the product to reach maximum effectiveness.

Storage temperature: between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

Data sheets are subject to change without notice. Revision date: September 2021.

FILA. Because It Works

Fila Chemicals USA, Corp. Miami, FL 33172

tel +1-305-513-0708 filausa@filasolutions.com





Recommended by over

200 INTERNATIONAL TOP BRANDS

manufacturers of materials for floors and wall coverings

filasolutions.com

TOLL FREE 1-844-FILA123