



LATICRETE® Heavy Duty Coating Stripper

DS 373.0-0716

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

LATICRETE® Heavy Duty Coating Stripper

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA
Telephone: +1.203.393.0010
Toll Free: +1.888.786.6343
Fax: +1.203.393.1684
Website: www.laticrete.com

3. PRODUCT DESCRIPTION

Uses

- Walls
- Floors

Advantages

- Easy-to-use water-based formula
- Maximum strength formula
- Low odor and non-flammable

Recommended Surfaces

Natural stone, tile and masonry surfaces, including:

- Marble
- Slate
- Saltillo tile
- Ceramic tile
- Porcelain tile

Not intended for use on surfaces other than stone, tile and masonry.

Item Numbers and Packaging

D15061213 – Quart 32oz (946 mL), 4 units per Case, 640 units per Pallet

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

VOC Content

9.9%

Storage and Handling Instructions

MAY BE HARMFUL IF SWALLOWED. CAUSES EYE IRRITATION. MAY CAUSE SKIN AND RESPIRATORY IRRITATION. Do not ingest. Avoid prolonged exposure to vapors. Use in a well-ventilated area. Rubber gloves and eye protection should be worn during handling and application to prevent skin and eye contact. KEEP OUT OF REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not flush unused product to natural waterways or sanitary sewer system. Dispose of in accordance with waste disposal regulations.

Cautions

Consult SDS for more safety information.

- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if respiratory irritation, nausea, or dizziness persists.
- Skin contact: Wash skin with soap and water. Seek medical attention if symptoms occur.
- Eye contact: Flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses if present and easy to do. Seek medical attention immediately.
- Ingestion: Rinse mouth. Do not induce vomiting. Call poison control enter. Seek medical attention if discomfort continues.

4. TECHNICAL DATA

Physical Properties

Form	Liquid
Color	Clear
Odor	Mild
pH	11.5

5. INSTALLATION

Directions

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results. Make sure all surfaces to be cleaned are swept or vacuumed to remove loose debris. Avoid skin and eye contact with product. Wear protective eyewear and rubber gloves when handling product. Ensure work area is well-ventilated during application and

until surface is dry. Keep children and pets out of the area until surface traffic resumes. Avoid applying in direct sunlight. LATICRETE® Heavy Duty Coating Stripper should not be used in extreme temperatures. Recommended application temperature range is 50°F – 90°F (10°C– 32°C).

1. SHAKE WELL BEFORE USING. Do not dilute before applying. Liberally apply an even coat of LATICRETE® Heavy Duty Coating Stripper over the required area with a paint brush, mop, or paint pad. DO NOT APPLY PRODUCT WITH A SPRAYER. Immediately remove product from unintended surfaces with a wet cloth to prevent potential damage to those surfaces.
2. Application times will vary depending on type of coating being removed. The following are approximate times:

Sealer, wax and varnish	30 to 60 minutes
Polyurethane and acrylic	1 to 2 hours
Epoxy grout haze	1 to 2 hours

3. Do not let LATICRETE® Heavy Duty Coating Stripper dry on the surface. If stripper starts to dry, moisten with additional product to keep surface wet.
4. Lightly rub surface with a nylon scrub brush or pad. Surface can be wet with water to enable easier removal of coating.
5. Wipe up residual coating with clean cloths.
6. Rinse surface well with clean water.
7. More than one application may be required. Repeat steps 2 through 7 when necessary.
8. Surface traffic may begin 2 hours after removal of coating.

Cleaning

Clean all tools used during application with water.

6. AVAILABILITY AND COST

Availability

LATICRETE®, STONETECH and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

www.stonetech.com or **www.laticrete.com**

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as Stone & Tile Floor Cleaner is recommended. For tough or difficult to remove soil use Heavy Duty Stone & Tile Floor Cleaner and a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at **www.laticrete.com** or **www.stonetech.com**.

10. FILING SYSTEM

Additional product information is available on our website at **www.stonetech.com**. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 370.5: Stone & Tile Floor Cleaner

DS 372.5: Heavy Duty Stone & Tile Floor Cleaner