

# Ready-To-Use Grout

## DESCRIPTION

ImmediaTile Grout is a premixed grout specifically designed for use with ImmediaTile system that delivers durable, stain resistant grout joints. This grout is for residential use in intermittently wet as well as dry areas. It can also be used to grout over existing premixed or cementitious grout installations. ImmediaTile Grout is formulated with very fine particles of sand and may be used in grout joints as small as 1/16" (1.6 mm). (Please see limitations regarding surfaces that might be sensitive to scratching).

### Key Features and Benefits

- For use with tile and luxury vinyl tile
- Grouts joints from 1/16" to 3/8" (1.6 mm to 9 mm)
- Highly stain resistant, no need to seal
- Mold and mildew resistant
- Durable, wear resistant
- Water resistant, can use in showers
- Easy to use

### Packaging

1/2 Gallon (64 Fl. Oz.) 1.89 L Plastic Pail

Retail Height:	6" (15.2 cm)
Retail Width:	6.5" (16.5 cm)
Retail Depth:	6.5" (16.5 cm)
Items per Case	4
Case Height:	6.5" (16.5 cm)
Case Width:	13" (33 cm)
Case Depth:	13" (33 cm)
Cases per Pallet:	63
Pallet Weight:	1,870 lbs. (About 848 Kg.)

### Colors

• Beige	Product # 15036431
• White	Product # 15036432
• Gray	Product # 15036434

### Coverage

Figures shown in the chart are presented only as guidelines.

Approximate Coverage in ft² (m²)				
Tile Size	Joint Width			
	1/16" (1.6 mm)	1/8" (3 mm)	1/4" (6 mm)	3/8" (9 mm)
4" x 4" x 1/8" (100 x 100 x 3 mm)	17.2 (1.60)	15.9 (1.48)		
6" x 24" x 5/16" (150 x 600 x 8 mm)	36.8 (3.42)	31.2 (2.90)	23.9 (2.22)	19.4 (1.80)
12" x 12" x 1/4" (300 x 300 x 6 mm)	47.8 (4.44)	41.5 (3.86)	32.9 (3.06)	27.3 (2.54)
12" x 24" x 3/8" (300 x 600 x 9 mm)	59.2 (5.50)	49.0 (4.55)	36.4 (3.38)	29.0 (2.69)

### Storage

Store indoors in a cool, dry location. Keep away from excessive heat. Freeze/thaw stable to -9.4°F (-23°C). If frozen, slowly bring material back to room temperature and mix per instructions.

## Shelf Life

Maximum of 18 months from date of manufacture in unopened package. Product good for 6 months after opening as long as bucket is re-sealed carefully and stored in a cool, dry, interior location and used within shelf life. Covering with plastic wrap directly on top of product prior to sealing container will help preserve freshness.

## Limitations

- Not for shower floors.
- Not for submerged applications.
- Not for exterior use.
- Not for use with polished marble, metal tiles and most glass tiles\*, travertine or Saltillo tile.
- Certain tile surfaces may be stained when grouted with colored grout. Follow tile manufacturer recommendations or test.
- Use on grout joints from 1/16" (1.6 mm) up to 3/8" (9 mm) wide.
- Do not grout over existing epoxy grout installations.
- Maintain temperature range of 60°-100°F (16°-32°C) during use and drying.
- Freeze-thaw stable. If frozen, thaw completely and remix before using.
- Not for use in swimming pools or exterior applications.
- Do not add water.
- Do not seal grout.

\*If sanded grout is appropriate with your glass tile, we recommend the use of ImmediaTile Grout.

## Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered ImmediaTile brand product(s) under normal environmental and working conditions. Because each project is different, ImmediaTile cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

## TECHNICAL DATA

### Applicable Standards

ImmediaTile Grout	
Description	Typical Results
Compressive Strength 28 day cure 21 day cure, 7 day soak	799 psi (5.47 MPa) 249 psi (1.70 MPa)
Flexural Strength 28 day cure	536 psi (3.67 MPa)
Tensile Strength 28 day	541 psi (3.70 MPa)

### Physical Properties

Description	
Physical State	Paste
Color	Available in 3 standard colors
Initial Cure [at 72°F (22°C)]	24 hours

# Grout

Description	
Final Cure	7 days
VOC/Liter of Material	28.1 grams less water and exempt compounds
Foot Traffic Rating (ASTM C627)	Residential
Storage	Store indoors in cool, dry location. Do not store open containers. Freeze/thaw stable to -10°F (-23°C).
Shelf Life	Maximum 18 months from date of manufacture in properly stored, unopened package.

## INSTALLATION INSTRUCTIONS

### Surface Preparation

Area must be clean, dry, free of dirt and dust. Grout joint should be free of sealers.

### Application

1. For best results, grout no more than 10 ft<sup>2</sup> (0.93 m<sup>2</sup>) at a time.
2. Press grout diagonally into joints holding float at a 45-degree angle. Make sure that joints are completely filled.
3. Remove all excess grout off tile by holding float at a 90-degree angle and drawing diagonally across tile.
4. For best results, wait 10 minutes before beginning clean up to allow the grout joint some time to firm up so it is not pulled out of the joint during clean up process. Do not wait longer than 40 minutes.
5. To clean, first soak sponge in cool clean water. Wring out most excess water, then pat the surface of the tile with the damp sponge to loosen the film. Next, rinse the sponge in water a second time and wring out excess water completely.
6. Use the damp sponge in a light, circular motion to smooth joints and clean film from the tile. Avoid using excessive amounts of water on the grout joints.
7. Turn sponge over to a clean side and draw diagonally across tiles to remove any remaining film.
8. For optimal results, follow these final clean-up steps: moisten a towel with clean water, wring out excess, then drag damp towel across surface diagonally. This will pick up remaining film.
9. If a light haze remains after cleaning, do not attempt to remove it with the sponge. Instead, leave the haze on the surface and remove the next day with a damp sponge. Haze will easily come off of most tile surfaces.
10. There is no need to seal ImmediaTile Grout.

NOTE: If excess water is used in the sponge during clean up, minor cracks or pinholes can develop. If the grout is over-worked, it may appear to shrink down into joint. Should any of these things occur, simply apply a second coat to the affected areas. You must allow your initial application to cure for 24 hours prior to your second application.

### Instruction For Use Over Premixed and Cement-Based Grout

To install, existing premixed or cementitious grout must be clean, sealer free, and 1/8" (3 mm) lower than tile surface. If not: Remove existing grout with a grout saw to at least 1/8" (3 mm) below the surface of the tile.

Make sure the joint is free of all dust and debris, then apply grout per instructions above.

### Set-up Time

Light foot traffic after 24 hours. Allow 7 days to achieve final cure which includes hardness and stain resistance. ALLOW 7 DAYS BEFORE EXPOSURE TO WATER.

### Clean-up

Clean tools and hands with warm soapy water while grout is still wet.

### Maintenance

For routine cleaning of your grout, use a Neutral pH cleaner. Follow manufacturer instructions for dilution. Do not use acids, bleaches or vinegar for cleaning. Alkaline-based cleaners can be used for periodic heavy duty cleaning. Follow manufacturer instructions for dilution.

## LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **H.B. Fuller Construction Products Inc. disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details, visit [www.immediatile.com](http://www.immediatile.com). To obtain a hard copy of the Limited Warranty call 1-800-832-9023 or mail a written request to H.B. Fuller Construction Products, 1105 S. Frontenac St. Aurora, IL 60504.