

Mira Strip

Fast Acting Floor Coating/Wax Stripper For

Polished, Honed & Textured Surfaces Including:

- | | | | |
|------------|----------------|---------------|------------|
| ■ Marble | ■ Granite | ■ Limestone | ■ Terrazzo |
| ■ Concrete | ■ Ceramic Tile | ■ Quarry Tile | ■ Grout |

Uses

- Interior & Exterior

Special Features

- Fast Acting ■ Easy-to-Use ■ Cost Effective

PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. Mira Strip is a fast acting, stripper designed to remove traditional solvent base coatings and waxes for preparation of one of the **Miracle Penetrating Sealers and/or Color Enhancement products.** Mira Strip will effectively remove **Mira Matte** color enhancer when necessary and may be effective for removing some food greases, tar and other hard to remove stains from tile, grout and stone surfaces. **Not for use on resin base products including polyester and epoxy agglomerates, terrazzo and grouts.**

Special Note: Mira Strip has a strong odor and should be used in a well ventilated area.

Sample Testing

Due to the differences of each material, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non masonry surfaces.

APPLICATION INSTRUCTIONS

Read entire label and SDS/PDS before using. This product should be used directly from container and is not under any circumstances to be thinned or diluted with anything before use.

Apply **Mira Strip** full strength to the surface with a clean mop. Be sure to completely saturate the surface being cleaned. Allow solution to sit on the surface for 10 - 20 minutes agitating periodically with the appropriate strip-ping pad or brush. Do not allow **Mira Strip** to dry on the surface. Agitate area one last time while adding more product and removing remains. Remove all **Mira Strip** from the surface with a wet vacuum or clean, dry towels. More than one application may be necessary to remove accumulated buildup. Thoroughly rinse completed area with clean water and allow to dry. Pour clean water on area being cleaned and agitate one last time before extracting all the dirty remains with a wet vacuum system. Note: Always allow used towels to completely dry before discarding. Once the coating and/or wax has been removed an additional deep cleaning may be necessary. For this procedure use the appropriate **Miracle Cleaner** as directed for each surface. (See the product chart).

Heavy Duty Cleaning: To remove lime, hard water deposits, efflorescence, grout haze, rust and other heavy dirt and grime use **Phosphoric Acid Cleaner** or **HDAC (Heavy Duty Acidic Cleaner)** or as directed. **Do not use HDAC, Phosphoric Acid Cleaner on polished marble, limestone or any acid sensitive stone or tile.** If an additional deep cleaning is necessary use **Liquid Powlitice** cleaner as directed. All strippers and/or cleaners should be thoroughly rinsed with clean water and the materials allowed to dry.

For a non-acid deep clean, use **Liquid Powlitice** as directed.

Light Duty Cleaning: Use **Tile & Stone Cleaner, Porcelain & Ceramic Tile Cleaner, Counter Kleen** or **Limestone/Travertine Soap** as directed.

Residue Removal

To remove accumulated **511 Sealer** residue, use **Residue Remover** as directed.

Color & Gloss Enhancement

For color and gloss enhancement, refer to the product recommendation chart.

Water, Stain & Slip Protection

To protect cleaned area from future soiling and staining and increase static coefficient of friction, we recommend applying the appropriate **Miracle Penetrating Sealer/Impregnator**.

Coverage

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, **Mira Strip** will cover 200 - 300 square feet per gallon (18 - 27 square meters per 3.785 liters).

MAINTENANCE

For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide.** Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

Storage

Store **Mira Strip** in the original container, properly sealed and unmixed. Stored at 77° F (25° C), Mira Strip will have a shelf life of 12 months. Do not allow to freeze.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901 or 626-443-6433 ext. 3013

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
1-626-443-6433 or 1-800-350-1901 • Fax: 1-626-443-1435
website: www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

Mira Strip contains petroleum distillate. All solvents must be considered toxic and must be used in a well ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of area until product or surface has thoroughly dried. **Refer to the SDS for additional information.**