



# NXT® Primer

DS-502-1120

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

NXT® Primer

## 2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: [laticrete.com](http://laticrete.com)

## 3. PRODUCT DESCRIPTION

NXT Primer is a concentrated premium quality, water-based primer designed to be applied prior to the installation of NXT Underlayments. NXT Primer penetrates deeply into substrates and maximizes bond strength.

### Uses

- With NXT Underlayments
- Interior Applications Only

### Advantages

- NXT Primer is multi-purpose and can be used on a wide range of substrates.
- NXT Primer may be broom, roller, or spray applied.
- Direct replacement for DRYTEK LEVELEX Primer

### Suitable Substrates

- Cement Backer Board
- Cement Mortar Bed
- Cement Terrazzo

- Ceramic Tile and Stone
- Concrete
- Vinyl Tile
- Exterior Glue Plywood (Interior Only)

### Packaging

4X1GAL (4X3.8L) JUG / 28 cartons per pallet /

Part: 0905-0401-2

5GAL (19L) PAIL / 36 per pallet /

Part: 0905-0005-2

245GAL (927.4L) TOTE /

Part: 0905-0245-2

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for one (1) year if stored at temperatures >32°F (0°C) and <95°F (35°C). do not allow to freeze (35°C).

### Limitations

- Do not install when surface temperature is below 40°F (4°C), when ambient temperature is expected to be below 50°F (10°C) during placement or before material takes final set or when temperature will be above 90°F (32°C).
- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE Waterproofing Membrane on top of the dry NXT underlayment.
- Do not install NXT Primer or underlayments over particleboard, chipboard, hardboard (Masonite), Luan panels, asbestos, interior glue plywood, gypsum-based patching materials, asphalt, coal tar, or lightweight insulating concrete or any other dimensionally unstable materials.
- Not for submerged applications.

### Cautions

- Read and understand the Product Data Sheet and Safety Data Sheet.
- Perform a mock-up to ensure product will perform as required.
- Check [www.laticrete.com](http://www.laticrete.com) for any technical bulletins or updated information about the product and its application.

- NXT PRIMER is water based. In case of eye contact, wash immediately with water. Get medical attention if eye irritation persists.
- Wear gloves and protective goggles.
- When spraying the product, avoid breathing the fine mist and use a NIOSH approved respirator.
- Contact your local LATICRETE Technical Sales Representative with any questions.
- Keep out of reach of children.

or providing quality control on the jobsite.

### **Cleaning**

All tools and equipment should be cleaned promptly with water.

## **4. TECHNICAL DATA**



### **VOC/LEED Product Information**

Meets all Federal, State & Local requirements for VOC. Actual field performance will depend on installation methods and site conditions. Specifications are subject to change without notification. Technical data shown in LATICRETE product data sheets and technical data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary greatly due to variability of critical job site factors.

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## **5. INSTALLATION**

### **Surface Preparation**

- Refer to TDS230 Substrate Preparation and Primer Guide for LATICRETE Self-Leveling Products for more detailed substrate preparation instructions.
- NXT® self-leveling underlayments shall be installed over NXT Primer once cured; typically, 3 to 5 hours after application depending on ambient and substrate conditions. Refer to TDS230 Substrate Preparation and Primer Guide for LATICRETE Self-Leveling Products.

### **Mixing**

NXT® Primer is a concentrate and must be diluted with clean potable water. Dilution ratio varies depending on the substrate. Mix/stir concentrate thoroughly prior to diluting.

### **Application**

For proper application instructions refer to TDS230 SUBSTRATE PREPARATION AND PRIMER GUIDE for LATICRETE SELF-LEVELING PRODUCTS. Field visits by LATICRETE personnel are for the purpose of making technical recommendations only and not for supervising

### **Coverage**

Approximate Yield, Dilution, and Spread Rate				
SUITABLE SUBSTRATES	Approximate Yield of Concentrate per gallon <sup>1</sup>	Dilution Ratio = Primer: Water	Approximate Spread Rate Diluted with Water <sup>2</sup>	<b>WATER DROP TEST</b> To help determine the appropriate primer dilution, please see TDS230 Substrate Preparation and Primer Guide for LATICRETE Self-Leveling Products
Normal Suction:	400 ft <sup>2</sup> (37 m <sup>2</sup> )	1:3	100 ft <sup>2</sup> (9 m <sup>2</sup> )	
High-Suction: • Dry Concrete • LATICRETE SLU • Cement Mortar Beds • Gypsum underlayment	200 ft <sup>2</sup> (19 m <sup>2</sup> )	1 <sup>st</sup> Coat: 1:5 2 <sup>nd</sup> Coat: 1:3	50 ft <sup>2</sup> (5 m <sup>2</sup> )	
Exterior Glue Plywood	200 ft <sup>2</sup> (19 m <sup>2</sup> )	1:1	100 ft <sup>2</sup> (9 m <sup>2</sup> )	
Non-Suction: • Ceramic • Stone • Quarry Tile • VCT • Sheet Vinyl • Terrazzo	200 ft <sup>2</sup> (19 m <sup>2</sup> )	1:1 with Slurry	100 ft <sup>2</sup> (9 m <sup>2</sup> )	
NXT Vapor Reduction Coating <sup>3</sup>  Vapor Ban Primer ER <sup>3</sup>	200 ft <sup>2</sup> (19 m <sup>2</sup> )	1:1 with slurry	100 ft <sup>2</sup> (9 m <sup>2</sup> )	
STRATA_MAT™  STRATA_HEAT™ Mat	n/a	n/a	n/a	
1. Approximate yield in square feet per gallon of concentrated primer. Use this column to estimate gallons of NXT Primer to purchase. 2. Approximate spread rate in square feet per gallon of diluted primer. Use this column to guide spread rate of the diluted primer. 3. Primer is not needed if used over moisture mitigation epoxies with sand broadcast.				* Do not use primer over STRATA_MAT or STRATA_HEAT Mat

NXT Primer is sold as a concentrate

## 6. AVAILABILITY AND COST

### Availability

LATICRETE materials are available worldwide.

**For Distributor Information, Call:**

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

[laticrete.com](http://laticrete.com)

**Cost**

Contact a LATICRETE Distributor in your area.

**7. WARRANTY**

See 10. FILING SYSTEM:

- DS 025.0: 25 Year System Warranty
- DS 230.05: 5 Year System Warranty
- DS 230.10: 10 Year System Warranty
- DS 230.13: 1 Year Product Warranty
- DS 230.99: LATICRETE Lifetime System Warranty (United States and Canada)

**8. MAINTENANCE**

Non-finish LATICRETE and LATAPOXY installation materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

**9. TECHNICAL SERVICES****Technical Assistance**

Information is available by calling the LATICRETE

Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

**Technical and Safety Literature**

To acquire technical and safety literature, please visit our website at [laticrete.com](http://laticrete.com).

**10. FILING SYSTEM**

Additional product information is available on our website at [laticrete.com](http://laticrete.com). The following is a list of related documents:

- DS 230.13: LATICRETE 1 Year Product Warranty
- DS 230.05: LATICRETE 5 Year System Warranty
- DS 230.10: LATICRETE 10 Year System Warranty
- DS 025.0: LATICRETE 25 Year System Warranty
- DS 230.99: LATICRETE Lifetime System Warranty
- DS 507.0: NXT® Vapor Reduction Coating
- TDS 230: Substrate Preparation and Primer Guide for LATICRETE Self-Leveling Products

---

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)

© 2020 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.