## MATERIAL SAFETY DATA SHEET

This MSDS complies with 29 CFR 1910.1200 (OSHA Hazard Communication Standard) and Canadian WHMIS Regulations.

IMPORTANT: Read this MSDS before handling and disposing of this product.

Pass this information on to employees, customers and users of this product.

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identity: Protecto Flex** 

**HMIS Hazard Ratings** 

Intended Use: Construction Waterproofing Material

Health 1\*

Fire 1

**Manufacturer:** Protecto Wrap Company Reactivity 0

1955 South Cherokee Street

Denver, CO 80223

**Telephone**: (303) 777-3001

**Fax**: (303) 777-9273 **Internet**: www.protectowrap.com

Emergency Phone: CHEMTREC: (800) 424-9300

**MSDS Date of Preparation**: 10/17/02

Prepared by: Denese A. Deeds, CIH Industrial Health & Safety Consultants, Inc. Woodbridge, CT 203-929-3473

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	CAS No.	Amount	Exposure Limit
Asphalt (petroleum; bitumen)	8052-42-4	50-80%	0.5 mg/m3 TLV-TWA
Calcium Carbonate	1317-65-3	10-20%	5 mg/m3 PEL-TWA (respirable fraction) 10 mg/m3 TLV-TWA

**Non-Hazardous Components > 1%:** Resins and Polymers 10-30%

# 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This product is a black tape with no odor. Product is not flammable but will burn under fire conditions. May cause mild eye and skin irritation.

## 4. FIRST AID MEASURES

**EYE:** First check victim for contact lenses and remove if present. Flush victim's eyes with large quantities of water, holding the eyelids apart. Get medical attention if irritation persists.

**SKIN:** Remove contaminated clothing. Wash skin thoroughly with soap and water. If rash or irritation develop, get medical attention.

**INGESTION:** If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. Get medical attention.

**INHALATION:** If symptoms of exposure develop, remove victim to fresh air. If breathing is difficult or symptoms persist, get immediate medical attention.

## 5. FIRE FIGHTING MEASURES

FLASH POINT: >320° F

FLAMMABLE LIMITS: LEL: Not applicable UEL: Not applicable

**AUTOIGNITION TEMPERATURE:** Not determined

**EXTINGUISHING MEDIA:** Use foam or dry chemical to extinguish fire. Use fog nozzles if water is used. Water streams may cause violent eruptions and spread the burning of asphalt. Use water to cool fire exposed containers and structures.

**UNUSUAL FIRE OR EXPLOSION HAZARDS:** Product will burn if exposed to elevated temperatures or fire. Hot asphalt may ignite flammable mixtures on contact. Toxic vapors including hydrogen sulfide may be released upon combustion. Hydrogen sulfide vapors are heavier than air, may accumulate in low areas and flashback if ignited.

**SPECIAL FIRE-FIGHTING INSTRUCTIONS:** Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Do not allow run-off from fire fighting to enter drains or water courses.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes, ketones and unidentified organic compounds may be formed on combustion.

**EXPLOSION DATA** (sensitivity to mechanical impact or static discharge): None known.

# 6. ACCIDENTAL RELEASE MEASURES

Pick up and place into an appropriate container for disposal. If product becomes molten, allow product to cool before picking or scraping up.

## 7. HANDLING AND STORAGE

**HANDLING:** Avoid contact with the eyes and skin. This product is not intended to be heated but if product is heated provide adequate ventilation and avoid breathing vapors and mists. Wash with soap and water after use.

**STORAGE:** Store in a cool, well ventilated area away from excessive heat and sources of ignition.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**EXPOSURE GUIDELINES:** Refer to Section 2.

**ENGINEERING CONTROLS:** General ventilation should be adequate for normal use. For operations where the TLV may be exceeded, mechanical ventilation such as local exhaust may be needed to maintain exposure levels below applicable limits.

**RESPIRATORY PROTECTION:** None needed under ambient conditions. For situations where the product is heated, hydrogen sulfide may be released. In such conditions, a NIOSH approved positive pressure self-contained breathing apparatus is recommended. Gas masks or other air purifying respirators are not recommended for hydrogen sulfide due to its poor odor warning properties. Equipment selection depends on containment type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

**SKIN PROTECTION:** Avoid skin contact. Wear appropriate impervious gloves.

**EYE PROTECTION:** Safety glasses or goggles should be worn where contact is possible. **OTHER:** Wear long sleeved shirt and long pants to avoid skin contact. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE AND ODOR:** White Crepe tape with no odor.

PHYSICAL STATE: Solid

BOILING POINT: Not applicable VAPOR PRESSURE: Not applicable VAPOR DENSITY: Not applicable EVAPORATION RATE: Not applicable SOLUBILITY IN WATER: Insoluble BULK DENSITY: 15.723 pounds/gallon

**SPECIFIC GRAVITY: 1.883** 

pH: NA

MELTING POINT: 220°F (104°C) (Softening Point)
OCTANOL/WATER COEFFICIENT: No data available

**VOC CONTENT:** 0%

# 10. STABILITY AND REACTIVITY

**STABILITY:** Stable under normal storage and handling conditions.

**INCOMPATIBILITY:** Strong oxidizers. Avoid water if product is molten.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, sulfur oxides, hydrogen

sulfide, acrolein, aldehydes, ketones and unidentified organic compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

## **HEALTH HAZARDS:**

**INGESTION:** No adverse effects are expected from normal use. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**INHALATION:** No adverse effects expected at ambient temperatures. Vapors released from heating product may cause respiratory irritation. At elevated temperatures hydrogen sulfide may be released. The release of hydrogen sulfide gas in various concentrations may cause irritation of the eyes and respiratory tract, headache, dizziness, nausea and drowsiness. Exposure to high concentrations of hydrogen sulfide can cause respiratory arrest and death.

**EYE:** May cause irritation with redness, tearing and blurred vision. Contact with product at elevated temperatures may cause thermal burns.

**SKIN:** May cause irritation, defatting of the skin and dermatitis. Contact with product at elevated temperatures may cause thermal burns.

**SENSITIZATION:** This product is not expected to cause sensitization.

**CHRONIC/CARCINOGENICITY:** No adverse effects expected at ambient temperatures. Prolonged inhalation of asphalt smoke has been shown to cause bronchitis, pneumonitis and abscess formation in laboratory animals. Asphalt fume condensates have been shown to cause tumorgenic responses when repeatedly applied to the skin of laboratory animals. Prolonged inhalation of talc dust may cause lung damage (pulmonary fibrosis), however, the talc in this product is bound in a polymer matrix and dust

exposure would not be expected. Asphalt (petroleum, bitumen) is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B.

**MUTAGENICITY**: No adverse effects from available data.

**SYNERGISTIC PRODUCTS**: None specifically known.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Employees with pre-existing skin and respiratory disorders may be at increased risk from exposure.

#### **ACUTE TOXICITY VALUES:**

Asphalt: Oral Rat LD50 - >5.0 g/kg Skin Rabbit LD50 - > 2.0 g/kg Skin Rabbit LD50 - 14100 uL/kg

Calcium Carbonate: No acute toxicity data available

# 12. ECOLOGICAL INFORMATION

No ecotoxicity data is available for this product at this time.

## 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state and federal environmental regulations.

#### 14. TRANSPORT INFORMATION

#### **DOT HAZARDOUS MATERIALS DESCRIPTION:**

Proper Shipping Name: Not Regulated

UN Number: None

Hazard Class/Packing Group: None

Labels Required: None

## 15. REGULATORY INFORMATION

**CERCLA/SUPERFUND:** This product is not subject to CERCLA reporting requirements.

SARA HAZARD CATEGORY (311/312): Acute Health, Chronic Health

**SARA 313 INFORMATION:** This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None **EPA TSCA INVENTORY:** All of the ingredients in this product are listed on the EPA TSCA Inventory.

#### **CALIFORNIA PROPOSITION 65**

This product contains the following chemicals known to the State of California to cause cancer:

None

#### **CANADA:**

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

**CANADIAN WHMIS CLASSIFICATION:** Not a controlled product (manufactured article). **CANADIAN CEPA**: All the components of this product are listed on the Canadian DSL.

#### 16. OTHER INFORMATION

**NFPA RATING:** Health = 1 Fire = 1 Reactivity = 0 **HMIS RATING:** Health = 1\* Fire = 1 Reactivity = 0

**REVISION SUMMARY:** Section 1: Product Name

#### **NOTICE**

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control and therefore, users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein and does not relate to its use in combination with any other material or process.