Material Safety Data Sheet DuPont[™] Stone Sealer & Enhancer Version 2.1 Revision Date 02/22/2011 Ref. 130000102214 This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries. SECTION 1. PRODUCT AND COMPANY IDENTIFICATION DuPont[™] Stone Sealer & Enhancer : Product name MSDS Number 130000102214 Manufacturer DuPont : 1007 Market Street Wilmington, DE 19898 Product Information : 1-800-441-7515 (outside the U.S. 1-302-774-1000) Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139) : CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-527-3887) Transport Emergency SECTION 2. HAZARDS IDENTIFICATION Potential Health Effects Skin : May cause skin irritation. Eyes : May cause eye irritation. tearing, Blurred vision. Inhalation : Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema). Inhalation of aerosol or fine spray mist may cause serious respiratory problems., Effects of breathing high concentrations of vapour may include:, dizziness, confusion, incoordination, drowsiness, or unconsciousness, Ingestion Red blood cell destruction which could produce tiredness, rapid heartbeat, dizziness, pale skin, leg cramps, shortness of breath, jaundice (yellow tinge to skin and eyes) May cause:, Kidney effects, altered blood chemistry, Nasal irritation, inflammation with redness, tenderness or swelling, Respiratory effects. **Target Organs** : Blood Carcinogenicity None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen. 1/9

DuPont[™] Stone Sealer & Enhancer

Version 2.1

Revision Date 02/22/2011

Ref. 130000102214

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Water	7732-18-5	81 - 95 %
Modified Linseed Oil		5 - 15 %
2-Butoxyethanol	111-76-2	<2 %
Fluorinated Acrylic Copolymer		<2 %

CTION 4. FIRST AID ME	ASURES
Skin contact	: Wash off immediately with soap and plenty of water. Wash contaminated clothing before re-use.
Eye contact	: Rinse immediately with plenty of water for at least 15 minutes. Seek medical advice.
Inhalation	: Move to fresh air. Oxygen or artificial respiration if needed. Symptoms may be delayed. Call a physician immediately.
Ingestion	: Call a physician or poison control centre immediately. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
General advice	: When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Flammable Properties





714	
PuPont [™] Stone Sealer a	& Enhancer
ersion 2.1	
evision Date 02/22/2011	Ref. 130000102214
Flash point	: >110 ℃ (>230 ℉)
Thermal decomposition	 > 200 ℃ (> 392 ℃) To avoid thermal decomposition, do not overheat. Thermal decomposition can lead to release of irritating gases and vapours.
Fire and Explosion Hazard	: The product itself does not burn. Hazardous decomposition products formed under fire conditions. Hazardous combustion products: Hydrogen fluoride Carbon dioxide (CO2) Carbon monoxide Other hazardous decomposition products may be formed.
Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Firefighting Instructions	: Wear self contained breathing apparatus for fire fighting if necessary. Evacuate personnel to safe areas. Do not allow run-off from fire fighting to enter drains or water courses.
NOTE: Review FIRE FIGHTING	G MEASURES and HANDLING (PERSONNEL) sections before proceeding with clea
NOTE: Review FIRE FIGHTING up. Use appropriate PERSONA	G MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean AL PROTECTIVE EQUIPMENT during clean-up.
NOTE: Review FIRE FIGHTING up. Use appropriate PERSONA Safeguards (Personnel)	 G MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean AL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel to safe areas. Use personal protective equipment. Ventilate the area. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled
NOTE: Review FIRE FIGHTING up. Use appropriate PERSONA Safeguards (Personnel) Spill Cleanup	 G MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean AL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel to safe areas. Use personal protective equipment. Ventilate the area. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Do not discharge to streams, ponds, lakes or sewers. Avoid subsoil penetration.
NOTE: Review FIRE FIGHTING up. Use appropriate PERSONA Safeguards (Personnel) Spill Cleanup Accidental Release Measures	 G MEASURES and HANDLING (PERSONNEL) sections before proceeding with clear AL PROTECTIVE EQUIPMENT during clean-up. Evacuate personnel to safe areas. Use personal protective equipment. Ventilate the area. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Do not discharge to streams, ponds, lakes or sewers. Avoid subsoil penetration.



JPont [™] Stone Sealer	^r & Enhancer
rsion 2.1	
evision Date 02/22/2011	Ref. 130000102214
Handling (Physical Aspects)	 contaminated clothing before re-use. To avoid thermal decomposition, do not overheat. Thermal decomposition
	can lead to release of irritating gases and vapours. Do not spray near open flame or heated surface.
Storage	: Keep tightly closed in a dry, cool and well-ventilated place.
CTION & EXPOSURE CONT	ROLS/PERSONAL PROTECTION
CTION 8. EXPOSURE CONTI Engineering controls	ROLS/PERSONAL PROTECTION : Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi.
	: Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi.
Engineering controls Personal protective equipmer	 Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi. In case of mist, spray or aerosol exposure wear suitable personal respiratory
Engineering controls Personal protective equipmer Respiratory protection	 : Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi. in case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Engineering controls Personal protective equipmer Respiratory protection Hand protection	 : Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi. : In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. : Additional protection: Impervious gloves
Engineering controls Personal protective equipmer Respiratory protection Hand protection Eye protection	 Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Additional protection: Impervious gloves Wear safety glasses or coverall chemical splash goggles.
Engineering controls Personal protective equipmer Respiratory protection Hand protection Eye protection Skin and body protection Exposure Guidelines Exposure Limit Values 2-Butoxyethanol	 : Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. : Additional protection: Impervious gloves : Wear safety glasses or coverall chemical splash goggles. : Lightweight protective clothing

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

4 / 9

Material Safety Data Shee	et	
DuPont [™] Stone Sealer	^r & Enhancer	
Version 2.1		
Revision Date 02/22/2011	Ref. 130000102214	
SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES		
	 liquid milky, white ether-like 4.5 100 ℃ (212 ℉) 85 - 95 % 1.0 soluble 	
SECTION 10. STABILITY AND F Stability	SECTION 10. STABILITY AND REACTIVITY Stability : Stable under normal conditions.	
Conditions to avoid		
Hazardous decomposition products	: Carbon dioxide , Carbon monoxide, Hydrogen fluoride Incompletely burned carbon products Other hazardous decomposition products may be formed.	
SECTION 11. TOXICOLOGICAL DuPont [™] Stone Sealer & En Further information 2-Butoxyethanol Dermal LD50		
Dermal	: rabbit Bloody urine	
Oral LD50	: 300 mg/kg , rabbit	
Oral	: rat Abnormal decrease in number of red blood cells	
	5/9	



DuPont [™] Stone Sealer & Enhancer	
Version 2.1	
Revision Date 02/22/2011	Ref. 130000102214
Inhalation LC50	: 2.21 mg/l , rat
Inhalation	: rat Abnormal decrease in number of red blood cells
Skin irritation	: Skin irritation, multiple species
Eye irritation	: animals (unspecified species) irritant
Skin sensitization	: animals (unspecified species) Not a skin sensitizer.
Repeated dose toxic	ity : Oral animals (unspecified species) Liver effects, Kidney effects, Bloody urine
Carcinogenicity	: An increased incidence of tumours was observed in some laboratory animals but not in others.
Mutagenicity	: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Reproductive toxicity	: Animal testing showed effects on reproduction at levels equal to or above those causing parental toxicity.
Teratogenicity	: Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.
Fluorinated Acrylic Copolymer Oral LD50	: > 5,000 mg/kg , rat
Inhalation 4 h ALC	: 4.7 mg/l , rat
Skin irritation	: No skin irritation, rabbit
Eye irritation	: slight irritation, rabbit
Skin sensitization	: Did not cause sensitization on laboratory animals., mouse
Repeated dose toxic	ity : Oral - gavage rat Abnormal increase in white blood cells, nasal effects, Kidney effects,
	6 / 9

Material Safety Data Sheet DuPont[™] Stone Sealer & Enhancer Version 2.1 Revision Date 02/22/2011 Ref. 130000102214 Increased kidney weight Mutagenicity Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Teratogenicity : Animal testing showed no developmental toxicity. SECTION 12. ECOLOGICAL INFORMATION Aquatic Toxicity 2-Butoxyethanol 96 h LC50 : Fish (unspecified species) 1,490 mg/l Fluorinated Acrylic Copolymer 48 h EC50 Daphnia magna (Water flea) > 120 mg/l : Additional ecological information : Information given is based on data on the components and the ecotoxicology of similar products. SECTION 13. DISPOSAL CONSIDERATIONS Waste Disposal : In accordance with local and national regulations. SECTION 14. TRANSPORT INFORMATION Not classified as dangerous in the meaning of transport regulations. **SECTION 15. REGULATORY INFORMATION TSCA Status** Listed. : **TSCA Status** : This material contains one or more substances which are subject to a TSCA 7/9



DuPont [™] Stone Sealer	& Enhancer
Version 2.1	
Revision Date 02/22/2011	Ref. 130000102214
	Section 5 Consent Order or Significant New Use Rule (SNUR). This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D: Fluorinated Acrylic Copolymer PMN Number: P-08-751 Contact your local DuPont sales or technical representative for more information.
SARA 313 Regulated Chemical(s)	: 2-Butoxyethanol
CERCLA Reportable Quantity	 53 lbs Based on the percentage composition of this chemical in the product.: 2-Butoxyethanol
PA Right to Know Regulated Chemical(s)	: Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): 2-Butoxyethanol
NJ Right to Know Regulated Chemical(s)	: Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): 2-Butoxyethanol
SECTION 16. OTHER INFORMA	TION
The DuPont Oval Logo [®] and are registered trademarks or	DuPont [™] trademarks of E. I. du Pont de Nemours and Company or its affiliates.
Contact person	: MSDS Coordinator, DuPont Chemicals and Fluoroproducts, Wilmington, DE 19898, (800) 441-7515

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.



DuPont[™] Stone Sealer & Enhancer

Version 2.1

Revision Date 02/22/2011

Ref. 130000102214