

DuPont[™] Heavy Duty Grout Haze Remover

Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

DuPont[™] Heavy Duty Grout Haze Remover Product name

MSDS Number 130000033861

: DuPont Manufacturer

> 1007 Market Street Wilmington, DE 19898

Medical Emergency : Transport Emergency : : 1-800-441-7515 (outside the U.S. 1-302-774-1000) 1-800-441-3637 (outside the U.S. 1-302-774-1139)

CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

: DuPont Importer/Distributor

> 1007 Market Street Wilmington, DE 19898

Telephone : +1-800-441-7515 (outside the U.S. +1-302-774-1000)

SECTION 2. HAZARDS IDENTIFICATION

Potential Health Effects

Skin : Causes burns.

Eyes Corrosive, may cause permanent eye injury if not promptly treated.

Inhalation : Causes respiratory tract irritation.

Ingestion : Severe irritation of the mucous membranes causes vomiting, nausea and

burns. Aspiration hazard if swallowed - can enter lungs and cause damage.

Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC,

NTP, or OSHA, as a carcinogen.



DuPont[™] Heavy Duty Grout Haze Remover

Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Water	7732-18-5	85 - 92 %
Alcohol Ethoxylate		1 - 5 %
2-Aminoethanol	141-43-5	1 - 5 %
1-(2-Butoxy-1-methylethoxy)propan-2-ol	29911-28-2	1 - 5 %
Ethoxylated Quaternary Amine		1 - 5 %

SECTION 4. FIRST AID MEASURES

Skin contact : Wash off immediately with soap and plenty of water. Wash contaminated

clothing before re-use.

Eye contact : Rinse immediately with plenty of water for at least 15 minutes. Seek medical

advice.

Inhalation : Move to fresh air. Oxygen or artificial respiration if needed. Symptoms may be

delayed. Call a physician immediately.

Ingestion : Call a physician or poison control centre immediately. If swallowed, DO NOT

induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person.

General advice : When symptoms persist or in all cases of doubt seek medical advice.



Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

SECTION 5. FIREFIGHTING MEASURES

Flammable Properties

Flash point : does not flash

Thermal decomposition : $> 200 \degree C (> 392 \degree F)$

To avoid thermal decomposition, do not overheat.

Thermal decomposition can lead to release of irritating gases and vapours.

Fire and Explosion Hazard : The product itself does not burn. Hazardous decomposition products formed

under fire conditions. Hazardous combustion products Carbon dioxide (CO2) Carbon monoxide Other hazardous decomposition products may be formed.

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and

the surrounding environment.

Firefighting Instructions : Wear self contained breathing apparatus for fire fighting if necessary.

Evacuate personnel to safe areas. Do not allow run-off from fire fighting to

enter drains or water courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Evacuate personnel to safe areas. Use personal protective equipment.

Ventilate the area.

Spill Cleanup : Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Pick up and transfer to properly labelled

containers.

Accidental Release Measures : Do not discharge to streams, ponds, lakes or sewers. Avoid subsoil

penetration.

SECTION 7. HANDLING AND STORAGE



Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

Handling (Personnel) : Avoid breathing vapours or mist. Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the product. Wash

contaminated clothing before re-use.

Handling (Physical Aspects) : To avoid thermal decomposition, do not overheat. Thermal decomposition

can lead to release of irritating gases and vapours. Do not spray near open flame or heated surface.

Storage : Keep tightly closed in a dry, cool and well-ventilated place.

Protect from freezing.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : Use only in area provided with appropriate exhaust ventilation.

Personal protective equipment

Respiratory protection : In case of mist, spray or aerosol exposure wear suitable personal respiratory

protection and protective suit.

Hand protection : Additional protection: Impervious gloves

Eye protection : Wear safety glasses or coverall chemical splash goggles.

Skin and body protection : Lightweight protective clothing

Exposure Guidelines Exposure Limit Values

2-Aminoethanol

PEL: (OSHA) 3 ppm 6 mg/m3 8 hr. TWA

PEL: (OSHA) 3 ppm 6 mg/m3 8 hr. TWA

TLV (ACGIH) 6 ppm STEL

TLV (ACGIH) 3 ppm TWA

AEL * (DUPONT) 3 ppm 8 & 12 hr. TWA



Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

1-Butoxy-2-propanol

AEL * (DUPONT) 50 ppm 8 & 12 hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid
Color : light yellow
Odor : mild

pH : 11.5 - 12.5
Boiling point/boiling range : 100 ℃ (212 ℉)

Specific gravity : 1.07

SECTION 10. STABILITY AND REACTIVITY

Stability : Stable under normal conditions.

Conditions to avoid : To avoid thermal decomposition, do not overheat.

Incompatibility : Acids Strong oxidizing agents

Hazardous decomposition

products Incompletely burned carbon products

Other hazardous decomposition products may be formed.

: Carbon dioxide , Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

 $\mathsf{DuPont}^{^\mathsf{TM}}\,\mathsf{Heavy}\,\mathsf{Duty}\,\mathsf{Grout}\,\mathsf{Haze}\,\mathsf{Remover}$

Skin irritation : Corrosive

Alcohol Ethoxylate

Dermal LD50 : 2,000 - 5,000 mg/kg, rabbit



Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

Oral LD50 : 1,100 mg/kg , rat

Eye irritation : Severe eye irritation, rabbit

Skin sensitization : Does not cause skin sensitisation., guinea pig

Repeated dose toxicity : Dermal

rat

Skin effects, Thickening of skin

Oral rat

No toxicologically significant effects were found.

Reproductive toxicity : Evidence suggests the substance is not a reproductive toxin in

animals.

Teratogenicity : Evidence suggests the substance is not a developmental toxin in

animals.

2-Aminoethanol

Dermal LD50 : 1,017 mg/kg, rabbit

Oral LD50 : 1,098 mg/kg , rat

Inhalation : An LC50/inhalation/4h/rat could not be determined because no

mortality of rats was observed at the maximum achievable

concentration.

Eye irritation : Corrosive, rabbit

Skin sensitization : Does not cause skin sensitisation., guinea pig

Repeated dose toxicity : Oral

rat

No toxicologically significant effects were found.

Inhalation

rat

No toxicologically significant effects were found.



Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

Mutagenicity : Animal testing did not show any mutagenic effects.

Tests on bacterial or mammalian cell cultures did not show mutagenic

effects.

Reproductive toxicity : Animal testing showed no reproductive toxicity.

Teratogenicity : Animal testing showed no developmental toxicity.

1-(2-Butoxy-1-methylethoxy)propan-2-ol

Dermal LD50 : > 2,000 mg/kg, rat

Oral LD50 : 1,477 mg/kg , rat

Inhalation 4 h LC50 : 2.04 mg/l, rat

Eye irritation : rabbit

irritant

Skin sensitization : human

Not a skin sensitizer.

Repeated dose toxicity : Inhalation

rai

No toxicologically significant effects were found.

Oral - feed

rat

No toxicologically significant effects were found.

Dermal

rat

No toxicologically significant effects were found.

Mutagenicity : Did not cause genetic damage in cultured bacterial cells.

Did not cause genetic damage in cultured mammalian cells.

Did not cause genetic damage in animals.

Teratogenicity : Evidence suggests the substance is not a developmental toxin in

animals.

Ethoxylated Quaternary Amine

Oral LD50 : 580 mg/kg , rat



DuPont[™] Heavy Duty Grout Haze Remover

Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

Eye irritation : Severe eye irritation, rabbit

Skin sensitization : Does not cause skin sensitisation., guinea pig

Mutagenicity : Did not cause genetic damage in cultured bacterial cells.

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Alcohol Ethoxylate

96 h LC50 : Pimephales promelas (fathead minnow) 8.5 - 11 mg/l

48 h EC50 : Daphnia magna (Water flea) 2.7 - 12 mg/l

2-Aminoethanol

96 h LC50 : Cyprinus carpio (Carp) 349 mg/l

72 h ErC50 : Pseudokirchneriella subcapitata (green algae) 2.5 mg/l OECD Test

Guideline 201

72 h NOEC : Pseudokirchneriella subcapitata (green algae) 1 mg/l OECD Test

Guideline 201

48 h : Daphnia magna (Water flea) 50 mg/l Directive 67/548/EEC, Annex V,

C.2.

30 d : NOEC Oryzias latipes (medaka) 1.2 mg/l OECD Test Guideline 210

21 d : NOEC Daphnia magna (Water flea) 0.85 mg/l OECD Test Guideline

211

1-(2-Butoxy-1-methylethoxy)propan-2-ol

96 h : Poecilia reticulata (guppy) 841 mg/l

48 h : Daphnia magna (Water flea) 1,000 mg/l

Ethoxylated Quaternary Amine

96 h LC50 : Oncorhynchus mykiss (rainbow trout) 24 mg/l

72 h EC50 : Algae 1.6 mg/l



Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

> 48 h EC50 Daphnia magna (Water flea) 13 mg/l OECD Test Guideline 202

Environmental Fate

Alcohol Ethoxylate

Biodegradability : 80 %

Readily biodegradable.

Bioaccumulation : Bioaccumulation is unlikely.

2-Aminoethanol

IATA_C

Biodegradability : > 90 % OECD Test Guideline 301

Readily biodegradable.

Ethoxylated Quaternary Amine

Biodegradability : 11%

Not readily biodegradable.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal : In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN number : 2491

> Proper shipping name : Ethanolamine solutions

: 8

. ลบหเทg group Labelling No. UN number : 111 : 8 : 2491

Proper shipping name : Ethanolamine solution

Class : 8 Packing group : 111

Labelling No. : 8

UN number **IMDG** : 2491



Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

Proper shipping name : ETHANOLAMINE SOLUTION

Class : 8
Packing group : III
Labelling No. : 8

DOT - packages with <= 5 liters per inner packaging and <= 30 kg gross may ship as a Consumer Commodity. IMDG - packages with <=5 liters per inner packaging and <=30 kg gross may ship as Limited Quantity. IATA - packages with <=0.5 liters per inner packaging and <=1 liter per outer package may ship as Limited Quantity.

IATA - limit is 60 liters per package.

SECTION 15. REGULATORY INFORMATION

TSCA : On the inventory, or in compliance with the inventory

SARA 313 Regulated

Chemical(s)

: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

California Prop. 65 : Chemicals known to the State of California to cause cancer, birth defects or

any other harm: none known

PA Right to Know Regulated Chemical(s) : Substances on the Pennsylvania Hazardous Substances List present at

a concentration of 1% or more (0.01% for Special Hazardous

Substances): 2-Aminoethanol

NJ Right to Know Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substance List

present at a concentration of 1% or more (0.1% for substances

identified as carcinogens, mutagens or teratogens): 2-Aminoethanol

SECTION 16. OTHER INFORMATION

DuPontTM is a trademark of E. I. du Pont de Nemours and Company.

The DuPont Oval Logo is a registered trademark of E.I. du Pont de Nemours and Company.

Contact person : MSDS Coordinator, DuPont Chemicals and Fluoroproducts, Wilmington, DE



DuPont[™] Heavy Duty Grout Haze Remover

Version 4.0

Revision Date 10/30/2013 Ref. 130000033861

19898, (800) 441-7515

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.