



LATICRETE® Stone Sealer & Enhancer

DS 380.0-0616

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

LATICRETE® Stone Sealer & Enhancer

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010
Toll Free: +1.888.786.6343
Fax: +1.203.393.1684
Website: www.laticrete.com

3. PRODUCT DESCRIPTION

LATICRETE® Stone Sealer & Enhancer is an easy-to-use, two-in-one formula designed to deepen the stone's natural beauty and protect.

Uses (Interior Only)

- Countertops
- Backsplashes
- Floors
- Walls

Advantages

- Easy-to-use, water-based formula
- Deepens stone's natural beauty while protecting against stains
- Revitalizes and enhances dull, faded stone
- Safe for use on grout

Recommended Surfaces

Unpolished natural stone and grout surfaces such as:

- Slate
- Sandstone
- Textured stone
- Flamed stone
- Tumbled stone
- Limestone
- Flagstone
- Travertine
- Bluestone

Item Numbers and Packaging

D14636922 – Gallon 32oz (3.8 L) Container, 4 units per Case, 160 units per Pallet

D14940198 – Quart (946 mL) Container, 4 units per Case, 640 units per Pallet

Approximate Coverage

- Up to 250 ft² / gallon container (23 m² / 3.8 L)
- Up to 65 ft² / quart container (6 m² / 946 mL)

Expected Wear

Up to 5 years

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

VOC Content

<200 g/L (excluding water) For EPA purposes

<25 g/L (including water) For U.S. State purposes (Low Solids Coating)

Storage and Handling Instructions

WARNING: HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN, AND RESPIRATORY IRRITATION. Do not ingest. Avoid contact with eyes and skin. Avoid prolonged exposure to vapors. KEEP OUT OF REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not release to natural waterways.

Cautions

Consult SDS for more safety information.

- Inhalation: Remove affected person to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if discomfort persists.
- Skin contact: Wash skin with soap and water. Seek medical attention if symptoms occur.
- Eye contact: Flush eyes thoroughly with water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion: Rinse mouth. Do not induce vomiting. Seek medical attention if any discomfort continues.

4. TECHNICAL DATA

Physical Properties

Form	Liquid
Color	Milky White
Odor	Ether-Like
pH	4.5

Working Properties

Full Cure	24 – 72 hours
Surface Use	6 – 8 hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for at least 72 hours prior to application. Make sure surface is clean, thoroughly dry and free of waxes and coatings. Not recommended for exterior surfaces. Avoid skin and eye contact. Wear protective eyewear and gloves. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area during application and drying.

Directions

1. Shake well before using.
2. Mask off surfaces not intended to be treated.
3. Apply LATICRETE® Stone Sealer & Enhancer evenly and liberally using a paint pad, low-pressure chemical resistant sprayer, roller or brush. Avoid applying on unintended surfaces.
4. Allow LATICRETE Stone Sealer & Enhancer to penetrate surface for 15 – 30 minutes; denser stone may require maximum time to penetrate the surface. Spread excess over entire area for even penetration.
5. Thoroughly wipe surface dry with clean dry towels. DO NOT ALLOW EXCESS TO DRY COMPLETELY ON SURFACE.
6. A second coat may be needed for porous, absorbent surfaces or if a darker appearance is required. Apply a second coat 1 hour after initial coat following directions in steps 2 – 4.
7. A full cure is achieved after 24 – 72 hours. Surface traffic may begin in 6 – 8 hours. If needed sooner, cover the floor with red rosin paper to protect it until full cure has been achieved.
8. Clean tools used during application with water.

6. AVAILABILITY AND COST

Availability

LATICRETE®, STONETECH® and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at www.stonetech.com or www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as Stone & Tile Floor Cleaner is recommended. For tough or difficult to remove soil use Heavy Duty Tile & Grout Cleaner with a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com or www.stonetech.com.

10. FILING SYSTEM

Additional product information is available on our website at www.stonetech.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 370.5: LATICRETE Stone & Tile Floor Cleaner

DS 372.5: LATICRETE Heavy Duty Tile & Grout Cleaner