



# STONETECH® Grout Sealer

DS 377.5-0419

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

STONETECH® Grout Sealer

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010  
Toll Free: +1.888.786.6343  
Fax: +1.203.393.1684  
Website: [www.laticrete.com](http://www.laticrete.com)

## 3. PRODUCT DESCRIPTION

STONETECH® Grout Sealer is designed for cement based grout and protects against dirt, oil, and water-based stains. It is formulated to keep grout looking newer longer while providing ease of cleaning.

### Uses (Interior and Exterior)

- Countertops
- Backsplashes
- Floors
- Walls

### Advantages

- Provides protection against dirt, water, and oil-based stains
- Protects grout, making cleaning easier
- Easy-to-use, water-based formula
- Interior and Exterior Use

### Recommended Surfaces

Cement-based grout for ceramic, porcelain, and glass tile.

### Item Numbers and Packaging

ST330-0632 – Quart 32 oz (946 mL), 4 / Case

### Approximate Coverage

- Up to 30 linear ft/4 oz unit (9.1 linear meters/118 mL), depending on porosity of grout
- Up to 250 linear ft/quart container (76.2 linear meters/946 mL), depending on porosity of grout

### Expected Wear

Up to 3 years

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

### VOC Content

<300 g/L (excluding water) For EPA purposes  
<10 g/L (including water) Low Solids Coating

### Storage and Handling Instructions

CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Do not ingest. Avoid contact with eyes and skin. Avoid prolonged exposure to vapors. Use only in a well-ventilated area. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not release to natural waterways.

### Cautions

Consult SDS for more safety information.

- Inhalation: Remove affected person to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if respiratory irritation persists.
- Skin contact: Wash skin with mild soap and water. Get medical attention if skin irritation persists. Launder affected clothing before re-wearing.
- Eye contact: Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation persists.
- Ingestion: Rinse mouth. Do not induce vomiting. Call poison control center. Get medical attention if any discomfort continues.

## 4. TECHNICAL DATA

### Physical Properties

Form	Liquid
Color	Milky White
Odor	Mild
pH	7 – 8

### Working Properties

Full Cure	24 – 48 hours
-----------	---------------

Surface Use	4 hours
-------------	---------

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24 hour cure time to determine ease of application and desired results. Allow new grout installations to cure for at least 72 hours prior to application. Make sure surface is clean, thoroughly dry and free of waxes and coatings. Surface temperature should be 50°F – 80°F (10°C – 26°C). Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area until treated surface is dry.

### Directions:

1. Using a paint pad, roller, or brush, liberally apply STONETECH® Grout Sealer directly onto grout lines and joints to thoroughly soak the grout surface.
2. Allow sealer to completely penetrate into the grout, 5-15 minutes.
3. Liberally apply a second coat following steps 1-2.
4. Wipe up all the Grout Sealer from the surface of the tile using a clean, dry, lint-free, cotton towel.
5. If sealer was not completely removed during step 3, a residue may appear. To remove, use a white nylon pad dampened with sealer to re-emulsify/loosen residue, and then wipe surface completely dry with a clean absorbent towel.
6. A full cure is achieved after 24 – 48 hours. Surface Use may begin in 4 hours. If needed sooner, cover the floor with red rosin paper to protect it until full cure is achieved.
7. Clean tools during application with water.

## 6. AVAILABILITY AND COST

### Availability

LATICRETE®, STONETECH® and LATAPOXY® materials are available worldwide.

### For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [www.stonetech.com](http://www.stonetech.com) or [www.laticrete.com](http://www.laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## 7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

## 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use Heavy Duty Tile & Grout Cleaner and a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc.

installation, test a discrete area or scrap piece of tile to insure desired results.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [www.laticrete.com](http://www.laticrete.com) or [www.stonetech.com](http://www.stonetech.com).

## 10. FILING SYSTEM

Additional product information is available on our website at [www.stonetech.com](http://www.stonetech.com). The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 372.5: Heavy Duty Tile & Grout Cleaner

LATICRETE International, Inc.  
One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)  
©2016 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.