



SAFETY DATA SHEET

1. Identification

Product identifier Impregnator Pro® Sealer
Other means of identification None.
Recommended use Treatment of natural stone surfaces.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name LATICRETE International
Address 1 Laticrete Park, N
 Bethany, CT 06524
Telephone (203)-393-0010
Contact person Steve Fine
Website www.laticrete.com
Emergency phone number Call CHEMTREC day or night
 USA/Canada - 1.800.424.9300
 Mexico - 1.800.681.9531
 Outside USA/Canada
 1.703.527.3887

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3
Health hazards Skin corrosion/irritation Category 2
 Specific target organ toxicity, single exposure Category 3 narcotic effects
 Aspiration hazard Category 1
Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2
 Hazardous to the aquatic environment, long-term hazard Category 2
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Naphtha (petroleum), hydrotreated heavy	64742-48-9	90-98
Partially Fluorinated Acrylic Copolymer	Proprietary	1-5
n-Butyl acetate	123-86-4	1-5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
Skin contact	Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.
Ingestion	Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Skin irritation. Irritation of nose and throat. Irritating to mucous membranes. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Solvent vapors may form explosive mixtures with air.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not breathe mist or vapor. Avoid contact with skin and eyes. Local authorities should be advised if significant spillages cannot be contained. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Use personal protection recommended in Section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Dike the spilled material, where this is possible. Following product recovery, flush area with water. Cover with plastic sheet to prevent spreading. Absorb spillage with non-combustible, absorbent material.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Environmental precautions

7. Handling and storage

Precautions for safe handling

The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. Do not handle or store near an open flame, heat or other sources of ignition. Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Use only in well-ventilated areas. Avoid prolonged exposure. Wash thoroughly after handling. Handle and open container with care.

Conditions for safe storage, including any incompatibilities

Follow rules for flammable liquids. Keep away from heat, sparks and open flame. Store in cool place. Keep in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep this material away from food, drink and animal feed. Use care in handling/storage. Keep away from sources of ignition - No smoking.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m3
n-Butyl acetate (CAS 123-86-4)	PEL	100 ppm
		710 mg/m3
		150 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
n-Butyl acetate (CAS 123-86-4)	STEL	200 ppm
	TWA	150 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	400 mg/m3	
		100 ppm	
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3	
		TWA	200 ppm
			710 mg/m3
		150 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Follow standard monitoring procedures.

Appropriate engineering controls

Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment. Provide easy access to water supply or an emergency shower.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear goggles/face shield.
Skin protection	
Hand protection	Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves. Protective shoes or boots. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Wear chemical protective equipment that is specifically recommended by the Personal Protective Equipment manufacturer.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Remove and isolate contaminated clothing and shoes.

9. Physical and chemical properties

Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Colorless.
Odor	Mild hydrocarbon.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	339.8 °F (171 °C)
Flash point	125.6 °F (52.0 °C) Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.761
Solubility(ies)	
Solubility (water)	Slightly soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC (Weight %)	748 g/l

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable under normal temperature conditions. Risk of ignition.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, sparks, flames, elevated temperatures.
Incompatible materials	Strong oxidizing agents. Strong acids.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Vapors may cause drowsiness and dizziness.
Skin contact	Causes skin irritation.
Eye contact	May cause eye irritation on direct contact.
Ingestion	Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. Irritation of nose and throat. Irritating to mucous membranes.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Components	Species	Test Results
-------------------	----------------	---------------------

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Acute

Dermal

LD50	Rabbit	> 2000 mg/kg
------	--------	--------------

Inhalation

LC50	Rat	> 4.96 mg/l, 4 Hours
------	-----	----------------------

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

n-Butyl acetate (CAS 123-86-4)

Acute

Inhalation

LC50	Rat	2000 ppm, 4 Hours
------	-----	-------------------

Oral

LD50	Rat	10768 mg/kg
------	-----	-------------

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation May cause eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not a skin sensitizer.

Germ cell mutagenicity Not classified.

Carcinogenicity Not classified.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not classified.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Further information Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
Aquatic		
Algae	IC50	Algae 10 mg/l, 72 hours
Crustacea	EC50	Daphnia 10 mg/l, 48 hours
Fish	LC50	Fish 10 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol / water (log Kow)
n-Butyl acetate (CAS 123-86-4) 1.78

Mobility in soil No data available.

Mobility in general The product is insoluble in water.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Dispose of this material and its container at hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.

Hazardous waste code Waste codes should be assigned by the user based on the application for which the product was used.

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN3295
UN proper shipping name Hydrocarbons, liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy, n-Butyl acetate)
Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
Packing group III
Environmental hazards
Marine pollutant Yes
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions 144, B1, IB3, T4, TP1, TP29
Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242
ERG number 128

IATA

UN number UN3295
UN proper shipping name Hydrocarbons, liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy, n-Butyl acetate)
Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
Packing group III
Environmental hazards Yes
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3295
UN proper shipping name Hydrocarbons, liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy, n-Butyl acetate)
Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
Packing group III
Environmental hazards
Marine pollutant Yes
EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:
Partially Fluorinated Acrylic Copolymer
PMN Number: P-08-0643

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

n-Butyl acetate (CAS 123-86-4) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)
n-Butyl acetate (CAS 123-86-4)

US. New Jersey Worker and Community Right-to-Know Act

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)
 n-Butyl acetate (CAS 123-86-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)
 n-Butyl acetate (CAS 123-86-4)

US. Rhode Island RTK

n-Butyl acetate (CAS 123-86-4)

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	17-March-2015
Revision date	-
Version #	01
NFPA ratings	

**List of abbreviations**

References HSDB® - Hazardous Substances Data Bank
 Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.