



## Product Specification Sheet

### Vetta by Stonepeak

#### Tile – Luxe Dune Series

| SKU       | Description                              | Nominal Size | Thickness (mm) | Material (BOM) | Surface Finish | Edge      | Manuf. Process |
|-----------|------------------------------------------|--------------|----------------|----------------|----------------|-----------|----------------|
| 101343440 | Luxe Dune Matte Porcelain Tile           | 12 x 12      | 8              | Porcelain      | Matte          | Rectified | Inkjet         |
| 101317766 | Luxe Dune Matte Porcelain Tile           | 12 x 24      | 8              |                |                |           |                |
| 101317980 | Luxe Dune Matte Porcelain Tile           | 24 x 24      | 8              |                |                |           |                |
| 101317899 | Luxe Dune Matte Porcelain Tile           | 24 x 48      | 8              |                |                |           |                |
| 101317832 | Luxe Dune Matte Porcelain Tile           | 48 x 48      | 6              |                |                |           |                |
| 101318046 | Luxe Dune Hexagon Matte Porcelain Mosaic | 12 x 12      | 8              |                |                |           |                |
| 101318103 | Luxe Dune Stacked Matte Porcelain Mosaic | 12 x 12      | 8              |                |                |           |                |
| 101318186 | Luxe Dune Square Matte Porcelain Mosaic  | 12 x 12      | 8              |                |                |           |                |

#### Performance Properties

#### Test Methods

#### Test Results

|                                 |                                                                                                            |                   |
|---------------------------------|------------------------------------------------------------------------------------------------------------|-------------------|
| Dynamic Coefficient of Friction | ASTM C1028                                                                                                 | 0.5               |
| Water Absorption                | ASTM C373-16 ISO 10545-3                                                                                   | ≤0.5%(Impervious) |
| Surface Wear / Abrasion Value   | ASTM C1027-09 or ISO 10545-7 (Glazed);<br>ASTM C1243-93(2015) or ISO 10545-6 (Unglazed)                    | 4                 |
| Mohs Scratch Hardness           | 1 – Talc 2 – Gypsum 3 – Calcite 4 – Fluorite<br>5 – Apatite 6 – Feldspar 7 – Quartz 8 – Topaz              | 7                 |
| Breaking Strength               | ASTM C648-04 (2014): ≥275 lbf; ASTM C1505 (Maximo):<br>≥157 lbf for <7.5mm & ≥292 lbf for ≥7.5; ISO 10545- | ≥275              |
| Chemical Resistance             | ASTM C650                                                                                                  | Class A-0         |
| Freeze Thaw                     | ASTM C1026                                                                                                 | Resistant         |

#### Tile Applications & Features

|                                                                                                                       |                                                                                                                    |                                                                                                             |                                                                                                                           |                                                                                                                                                     |                                                                                                          |
|-----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| <br>Backsplash<br>Yes              | <br>Shower Wall<br>Yes          | <br>Shower Floor<br>Yes  | <br>Bathroom Floor<br>Yes             |                                                                                                                                                     |                                                                                                          |
| <br>Indoor Wall<br>Yes             | <br>Indoor Floor<br>Yes         | <br>Outdoor Floor<br>Yes | <br>Outdoor Wall and Countertop<br>Yes | <br>Color Body Tile<br>Yes                                     |                                                                                                          |
| <br>Radiant Heating Systems<br>Yes | <br>Pool Deck / Wet Areas<br>No | <br>Pool Interior<br>Yes | <br>Fireplace Surround<br>Yes          | <br>Floor Suitability Rating<br>All Residential/All Commercial | <br>Warranty<br>Yes |

The product specifications listed reflect data from the manufacturer or from laboratory testing performed under specific testing conditions. As such it does not represent all conditions under which the products may be used or subjected. Product specifications are subject to variation and tolerances within testing or productions and may vary. Variations in appearance, texture, construction, dimensions, performance, and style may occur and should be considered in product selection. For information on performance standards and/or suitability please consult the ANSI, ASTM, or Tile Council of North America resources.