



## Product Specification Sheet

### Vetta by Stonepeak

#### Tile – Luxe Smoke Series

SKU	Description	Nominal Size	Thickness (mm)	Material (BOM)	Surface Finish	Edge	Manuf. Process
101343408	Luxe Smoke Matte Porcelain Tile	12 x 12	8	Porcelain	Matte	Rectified	Inkjet
101317881	Luxe Smoke Matte Porcelain Tile	12 x 24	8				
101317931	Luxe Smoke Matte Porcelain Tile	24 x 24	8				
101317840	Luxe Smoke Matte Porcelain Tile	24 x 48	8				
101317998	Luxe Smoke Hexagon Matte Porcelain Mosaic	12 x 12	8				
101318053	Luxe Smoke Stacked Matte Porcelain Mosaic	12 x 12	8				
101318129	Luxe Smoke Square Matte Porcelain Mosaic	12 x 12	8				

#### Performance Properties

#### Test Methods

#### Test Results

Dynamic Coefficient of Friction	ASTM C1028	0.5
Water Absorption	ASTM C373-16 ISO 10545-3	≤0.5%(Impervious)
Surface Wear / Abrasion Value	ASTM C1027-09 or ISO 10545-7 (Glazed); ASTM C1243-93(2015) or ISO 10545-6 (Unglazed)	4
Mohs Scratch Hardness	1 – Talc 2 – Gypsum 3 – Calcite 4 – Fluorite 5 – Apatite 6 – Feldspar 7 – Quartz 8 – Topaz	7
Breaking Strength	ASTM C648-04 (2014): ≥275 lbf; ASTM C1505 (Maximo): >=157 lbf for <7.5mm & >=292 lbf for >=7.5; ISO 10545-	≥275
Chemical Resistance	ASTM C650	Class A-0
Freeze Thaw	ASTM C1026	Resistant

#### Tile Applications & Features



Backsplash

Yes



Shower Wall

Yes



Shower Floor

Yes



Bathroom Floor

Yes



Indoor Wall

Yes



Indoor Floor

Yes



Outdoor Floor

Yes



Outdoor Wall and Countertop

Yes



Color Body Tile

Yes



Radiant Heating Systems

Yes



Pool Deck / Wet Areas

No



Pool Interior

Yes



Fireplace Surround

Yes



Floor Suitability Rating

All Residential/All Commercial



Warranty

Yes

The product specifications listed reflect data from the manufacturer or from laboratory testing performed under specific testing conditions. As such it does not represent all conditions under which the products may be used or subjected. Product specifications are subject to variation and tolerances within testing or productions and may vary. Variations in appearance, texture, construction, dimensions, performance, and style may occur and should be considered in product selection. For information on performance standards and/or suitability please consult the ANSI, ASTM, or Tile Council of North America resources.