



TUB & TILE CAULK

SILICONIZED-ACRYLIC CAULK

KEY FEATURES

- Low VOC-Formula
- Interior and Exterior Use
- Durable, Flexible Seal

DESCRIPTION

This low-voc, one-part, premium, siliconized-acrylic caulk provides a flexible seal that bonds to most common household surfaces. Bostik Tub and Tile™ Caulk is designed to complement Bostik grout colors.

DIRECTIONS FOR USE

Read and understand datasheet completely before beginning installation. Always do a test to ensure product satisfaction and/or to become familiar with proper application techniques prior to use.

- For gaps up to 1/2" (12mm)**
- For filling joints where tile meets dissimilar surfaces.
- For caulking around sinks, tubs, showers, countertops, ceramic tile and natural stone.
- Ideal flexible joint between horizontal and vertical surfaces.

** Joint size should not exceed 1/2 inch X 1/2 inch; if joint exceeds 3/8 inch width X 1/4 inch depth, use appropriate closed-cell backer rod.

SURFACE PREPARATION

Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint & old caulking. Remove mildew by scrubbing with a solution of 4oz. TSP (Trisodium Phosphate), 1 quart of liquid bleach mixed with 3 quarts of warm water. Protect eyes and hands by wearing goggles and water & chemical-resistant gloves. Thoroughly rinse surface and allow to dry completely before caulking.

APPLICATION

Apply only when caulk, air and substrate temperatures are above 40°F(4°C). Cut cartridge nozzle at a 45° angle to desired size and puncture inner foil seal. For a neat, straight edge, mask both



sides of joint with painters tape. Insert cartridge into caulking gun. Apply caulking while holding at a 45° angle using steady even pressure. After installation the joint should be immediately smoothed with a spatula, spoon or wet finger to reduce voids and create a smooth appearance. Wipe away excess with damp cloth before surface skins over. Protect from water until cured (24 hrs.) May be painted over in 4-6 hours depending on climatic conditions. Larger beads may require longer drying time due to temperature and humidity.

TECH DATA

- Meets ASTM C834 for low-movement sealant
- Low VOC <1.5%/wt, < 25 g/l as calculated by CARB
- Flash point >200°F (93°C)
- Freeze / Thaw Stable
- UV-Stable
- Mold & Mildew Resistant

CLEAN UP

Clean all tools with soap and warm water. Remove cured caulk with a sharp blade. Clean your skin and equipment immediately after use with warm water and a mild soap.

APPROXIMATE COVERAGE CHART								
Coverage for 10.1 fl. oz. (298 ml) Cartridge								
Depth	Width							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	99	49	33	24	20	16	14	12
1/4"		24	20	12	10	8	7	6
3/8"			11	8	6	5	5	4
1/2"				6	5	4	3	3

Linear Feet per 10.1 fl. oz. Cartridge

FOR BEST RESULTS

- Apply caulk in temperatures between 50°F (10°C) & 90°F (32°C).
- Store caulk at temperatures between 40°F (4°C) F & 90°F (32°C).
- Do not use for automobile, marine or below waterline applications.
- Do not use for filling butt joints, correcting surface defects or for tuck pointing.
- Allow new concrete to cure for 30 days before caulking.
- Do not use for joints subject to heavy abrasion or wear.
- Do not attempt to thin caulk with solvents or water.
- Prime bare surfaces before caulking.
- For a neat, straight bead edge, mask both sides of joint with masking tape.
- Do not "overtool" the applied caulk, leaving too little caulk to perform properly.
- Allow a minimum of 4 to 6 hours drying time before painting.

STORAGE AND SHELF LIFE

Store in temperatures between 40°F (4°C) and 90°F (32°C). Shelf life is two years from the date of manufacturing.

PACKAGING

10.1 oz cartridges (6/case). Sold in full cases only. Available in most Bostik grout colors in sanded or unsanded formulas. Check with customer service or your Bostik Territory Manager.

LIMITATIONS

- Apply only to clean, dry, frost-free surfaces.
 - Do not apply when rain or freezing temperatures are expected.
 - Protect from rain and exposure to water for 72 hours.
 - Not recommended for use underwater or below grade.
 - Cold weather & high humidity will slow down cure time.
 - Not for use in joints subjected to high degrees of movement.
(Use Bostik ChemCalk 900, 1100FS or 955 SL).
 - NOT FOR USE IN STEAM ROOMS OR COMMERCIAL KITCHENS & SHOWERS (USE PURE SILICONE CAULK)
- ** Joint size should not exceed 1/2 inch X 1/2 inch; if joint exceeds 3/8 inch width X 1/4 inch depth, use appropriate closed-cell backer rod.

LIMITED WARRANTY

The Limited Warranty for this product can be found at www.Bostik-US.com/resource-center/warranties or by calling 1-800-726-7845 (choose option 2, then option 2 again). TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE TO CERTAIN CLASSES OF BUYERS AND SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

WARNING

CAUTION! CAUSES EYES AND SKIN IRRITATION. MAY BE HARMFUL IF INHALED. This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

PRECAUTIONS

Use with adequate ventilation. Avoid prolonged exposure to vapors. Avoid contact with skin and eyes.

FIRST AID

If overcome by vapors, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, flush skin and eyes with water. Call a physician if irritation persists.

BOSTIK HOTLINE
Smart help
1-800-726-7845

Bostik, Inc.
 11320 W. Watertown Plank Road
 Wauwatosa, WI 53226
 A company of TOTAL
www.bostik-us.com

