

## STEP 1: PREP

PREP SETS THE FOUNDATION FOR A GOOD INSTALLATION AND ADDS DURABILITY TO YOUR TILE AND STONE PROJECT.

### Self-Leveling

- NXT LEVEL PLUS & ULTRAPLAN 1 PLUS**
- Cement-based self-leveling for interior substrate
  - Ultraplan Plus can level 1/16" to 1 1/2" in a single application
  - NXT Level Plus can level 1/8" to 1 1/4" in a single application
  - Use in combination with the appropriate primer



### Prime

#### PRIMER T & NXT PRIMER

- Use to prime substrates before applying self-leveling underlayment



### Patch

#### NXT PATCH & MAPECEM QUICKPATCH

- Premium cement-based underlayment used for patching concrete surfaces
- Use for interior and exterior applications
- Quick-drying, sets in 60 mins or less



### Crack Isolation

#### FRACTURE BAN SC & MAPELASTIC CI

- Anti-fracture resistant to 1/8" in plane for cement subfloors
- Quick-drying
- Easily applied with roller or brush
- Convenient and versatile: bonds to a wide range of floor surfaces



#### STRATA MAT

- Eliminates the main cause of cracked tile on floor applications
- Install tiles immediately after setting
- Use either modified or non modified thinset



#### DITRA UNCOUPLING MEMBRANE

- Eliminates the main cause of cracked tile on floor applications
- Waterproof - protects the subfloor



### Waterproofing & Crack Isolation

#### HYDRO BAN & AQUADEFENSE

- Thin waterproofing and crack isolation membrane that does not require fabric
- Hydro Ban allows for flood testing in 2 hours. Aquadefense allows for flood testing in 12 hours
- Anti-fracture resistant to 1/8"
- Formulated with antimicrobial technology to prevent mold and mildew



#### HYDRO BAN SHEET MEMBRANE

- Waterproofing membrane for interior intermittent wet applications
- Use either a polymer modified or non-modified mortar



#### KERDI WATERPROOFING MEMBRANE

- Waterproofing membrane for interior intermittent wet applications
- Allows for flood testing in 24 hours
- Use only Schluter All-Set or a nonmodified mortar



### Surface Prep

#### PRIME-N-BOND & ECO PRIM GRIP

- Versatile, ready-to-use, low VOC primer enhances adhesion to smooth and difficult-to-bond substrates
- Improves bonding of cement self-levelers and mortar
- Single coat application applies with a roller or brush



#### SENTINEL CEMENT FOAM BOARD

- 1/2" Thickness available in 3x5 and 4x8
- Lightweight, easy to handle and transport
- Prevents mold and mildew
- CUPC certified



#### KERDI-BOARD

- 1/2" and 2" thick boards available in various sizes
- Prevents mold and mildew
- Lightweight, easy to handle and transport



### PREP TOOLS

- Goggles
- F&D bucket
- Knee Pads
- Painters Tape
- Backerboard Seam Tape
- Fiber Cement Shears
- Tape Measure
- Sponges
- Protector Paper
- Scraper
- Screws
- Backerboard Knife
- Roller Tray
- Laser Level

## STEP 2: SET

### Lightweight Mortar

#### MULTIMAX LITE & ULTRALITE

- Non-sag mortar for large format tiles
- Smooth, creamy, and easy-to-trowel consistency
- Floor and wall application



### Large Format Tile Mortar

#### 4-XLT & ULTRAFLEX LFT

- Best-in-class non-sag mortar formulated specially for large format tiles
- Floor and wall application
- Used for freeze/thaw applications
- Commercial / Residential



#### KERAFLEX PLUS

- Smooth, creamy formula is easy to install
- Non-sag and nonslump for wall and floors
- Commercial / Residential



### Thinset Mortar

#### 254 PLATINUM

- Superior bond strength
- Floor and wall application
- Extended open time
- Anti-microbial



#### ALL-SET

- Formulated for Schluter membranes
- Sag resistant
- Floor and wall application



### SET TOOLS

The bigger the tile, the bigger the notch trowel. The bigger the trowel, the more mortar. See associate for details.

- Chalk Line
- Paddle Mixer
- Margin Trowel
- Tile File
- Spacers
- Blade
- Wet Saw
- Suction Cup
- Trowel
- Tile Nippers
- Leveling System
- Manual Tile Cutter
- Table Top Wet Saw

## STEP 3: GROUT

### Specialty & Epoxy

#### SPECTRALOCK 1 & KERAPOXY CQ

- Professional grade, epoxy-performance grout
- No sealing or mixing required
- Non-sag, color consistent, stain resistant, and crack resistant
- Anti-Microbial



### Pre-Mixed Grout

#### FLEXCOLOR CQ & READY-TO-USE

- Ready to use grout that does not need to be sealed
- Provides consistent color
- Professional grade formula ideal for both floors and walls
- Installs faster than traditional grout



### Performance Grout

#### PERMACOLOR & ULTRACOLOR PLUS FA

- All-in-one grout replacement for sanded and unsanded grouts
- No sealing required, color consistent, and stain resistant



### Pre-Mixed Grout

#### FLEXCOLOR 3D & DIMENSIONS™

- Ready to use grout that provides a unique, reflective, modern finish for tile, stone, and glass installations
- No sealing required



### GROUT TOOLS

- Sponge
- Bucket
- Gloves
- Cheese Cloth
- Low Speed Mixer
- Spacer Remover
- Margin Float
- Grout Float
- Caulking Gun

## STEP 4: SEAL & MAINTAIN

### Penetrating Sealer

- Invisible barrier that resists stains and moisture
- Preserves the natural look of material
- For all stones and grouts
- Great for Marble



### Enhancing Sealer

- Invisible barrier that resists stains and moisture
- Enhances and deepens the look of material



### Stone & Tile Cleaner

- Daily Cleaners
- Ready-to-use Cleaners
- Concentrated & Heavy-Duty Cleaners
- Haze Remover



### SEAL & MAINTAIN TOOLS

- Eye Protection
- Respirator
- Applicator & Tray
- Gloves
- Sponge Pack
- Applicator Bottle
- Brush
- Microfiber Cloth