


Ultrabond Turf Tape

Premium Turf Seam Tape



DESCRIPTION

Ultrabond® Turf Tape is a PET-based, spun-bonded, nonwoven fabric tape designed specifically to work with MAPEI turf adhesives for seaming synthetic turf. *Ultrabond Turf Tape* is waterproof and provides superior tensile strength and tear resistance, which are vital for installations of professional athletic playing fields. It is also perfectly suited as a seaming base for other synthetic turf applications, including installations of residential landscaping, playgrounds and golf courses.

FEATURES AND BENEFITS

- Superior tensile and shear strength
- Perfectly suited for use with MAPEI turf adhesives
- Meets FIFA standards

INDUSTRY STANDARDS AND APPROVALS

- FIFA Joint Strength (EN 12228 and EN 13744): > 25N/100mm

WHERE TO USE

- Interior and exterior synthetic turf installations
- Professional and educational synthetic sports field arenas
- Commercial and residential landscaping applications of synthetic turf

LIMITATIONS

- Install only in areas recommended by the turf manufacturer.
- It is not recommended to seam synthetic turf upside down and "flip" the turf-and-seam-tape assembly, as this can put significant tension on the assembly and ultimately weaken it. If the turf-and-seam-tape assembly must be flipped, ensure that it is fully supported every 3 to 4 feet (0.91 to 1.22 m) to ensure that additional strain is not put on the overall assembly.

SUITABLE SUBSTRATES

- Properly prepared field base (per the turf manufacturer's specifications for compaction and drainage)
- Underlayment mat (approved by the synthetic turf manufacturer)

SURFACE PREPARATION

- All substrates must be prepared in accordance with the synthetic playing surface manufacturer for the type of intended use and must comply with current regulations and industry standards.
- All substrates must be structurally sound, dry, solid and stable.
- The substrate should be clean and free of dust, dirt, oil, grease, paint, curing agents, concrete sealers, loosely bonded toppings, loose particles, old adhesive residues, and any other substance or condition that may prevent or reduce adhesion.
- All surfaces must be level, even, flat and smooth.

PRODUCT APPLICATION

1. Synthetic turf must be unrolled and acclimated per the manufacturer's written instructions to allow reduction of internal tensions caused by packaging and transport.
2. Place *Ultrabond Turf Tape* at the turf seam line directly on the properly prepared base.
3. Select the proper MAPEI turf adhesive. Refer to the adhesive's Technical Data Sheet for complete installation instructions.
4. Install turf in strict accordance with the turf manufacturer's written instructions.

Note: Weights may be required on turf seams to ensure proper bonding and even thatch heights.

Product Performance Properties

Laboratory Tests	Results
Fabric type	PET
Color	White
Shelf life	2 years
Storage conditions	50°F to 90°F (10°C to 32°C)

Packaging

Size
Roll: 12" x 330 ft. (30 cm x 101 m)
Roll: 60" x 100 ft. (150 cm x 30.5 m)

ADDITIONAL INFORMATION

For information on MAPEI’s commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: January 29, 2025 MK 3000282 (24-3474)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.
All Rights Reserved. © 2025 MAPEI Corporation.

